



PERLIGHT
smart.black



PLM-310P-72 SERIES

Polycrystalline Silicon Solar Module

PERLIGHT SOLAR

Founded in 2006, Perlight is a Global Solar Energy provider with a presence in more than 80 countries around the world. More than 1.5GW of Perlight modules have been used in residential, commercial and off-grid systems around the world.

Perlight's success has been built on proven product performance and reliability, state of the art technology and long term partnerships with key customers.

18.2% - 20.2%
CELL EFFICIENCY

12 YEARS
PRODUCT WARRANTY

0 -3%
POWER TOLERANCE

POWER WARRANTY

25 YEAR 80% Power Output Warranty

12 YEAR 90% Power Output Warranty

12 YEAR Material & Workmanship Warranty



Performance

High output and efficiency even under low light conditions



Versatility

Salt mist corrosion tested, perfect for harsh climatic conditions



Reliability

Durable and reliable solar panels due to stringent quality control measures, testing and strict selection of raw materials and components. PID free (TUV certified)



Design and Innovation

Perlight is committed to innovation and constantly working to provide the next breakthrough in solar technology: the new All Black panel is an example of this commitment.

POLYCRYSTALLINE, 72-CELL SERIES

ELECTRICAL PERFORMANCE

Module type	PLM-310P-72									
Power output	P_{max}	W	310	315	320	325	330	335	340	
Power output tolerances	ΔP_{max}	%	0 - 3							
Voltage at Pmax	V_{mpp}	V	37	37.28	37.56	37.8	38.07	38.33	38.6	
Current at Pmax	I_{mpp}	A	8.38	8.45	8.52	8.6	8.67	8.74	8.81	
Open-circuit voltage	V_{oc}	V	45.45	45.6	45.82	46.08	46.41	46.83	47.13	
Short-circuit current	I_{sc}	A	8.85	8.91	9.03	9.08	9.13	9.16	9.23	
Solar Module Efficiency	Eff.	%	15.98	16.23	16.49	16.75	17.01	17.26	17.52	

STC: 1000W/m² irradiance, 25°C cell temperature, AM 1.5g spectrum according to EN 60904-3.

THERMAL CHARACTERISTICS

Nominal operating cell temperature	NOCT	°C	45±2
Temperature coefficient of Pmax	μ	%/°C	-0.40
Temperature coefficient of Voc	β_{Voc}	%/°C	-0.30
Temperature coefficient of Isc	α_{Isc}	%/°C	0.06
Temperature coefficient of Vmpp	β_{Vmpp}	%/°C	-0.35

OPERATING CONDITIONS

Max. system voltage	1000V _{DC}
Limiting reverse current	15A
Operating temperature range	-40°C to 85°C
Max. static load front (e.g., snow)	5400Pa
Max. static load back (e.g., wind)	2400Pa
Max. hailstone impact (diameter / velocity)	25mm / 23m/s

MECHANICAL CHARACTERISTICS

Front cover (material / thickness)	low-iron tempered glass / 3.2mm
Backsheet (color)	white
Cell (quantity / material / dimensions)	72 / polycrystalline silicon / 156 x 156mm
Frame (material / color)	anodized aluminum alloy / silver
Junction box (protection degree)	≥ IP67
Cables & Plug connectors	900mm / 4mm ² & MC4 compatible / IP67
Module Dimensions (L / W / H)	1956mm x 992mm x 40mm
Module Weight	21.6kg

PACKING DETAILS

Container	20'GP	40'HQ
Pieces per pallet	52	58
Pallets per container	5	11
Pieces per container	260	638



PERLIGHT
smart.black



Perlight Partners

QUALIFICATIONS & CERTIFICATIONS

IEC 61215, IEC 61730, CE, IEC 62804 (PID Free), UL 1703, J-PEC, PV CYCLE, IEC/EN 61701, IEC 62716



Module Diagram:



Electrical Curves:

