



LED BULB

Product & Family 001 001 0006

FONIX-6

Technical Data	
Voltage (V)	175-250V
Product Wattage (W)	6
Equivalence with incandescent lamp	48
Colour Render Index (Ra)	80
Colour Temperature (K)	3000K-4200K-6400K
Materials	Aluminium Housing with PMM Diffuser
Protection Class	-
Dimmable	No
EEI	
Warm-up time up to % of the full light output	60 % Instant Full Light
Luminous Flux (lm)	390
Luminous Efficacy (lm/W)	65
Rated Life (hrs)	25,000
IP Rating	-
Power Factor	>0.5
Beam Angle	105°
Starting Time	<0.5
Number of ON-OFF cycles	>12500




Technical Drawing



Photometric Diagram

Applications

- The luminaire is an excellent solutions for market, museum other spot lighting needed.

	12.500X ON / OFF		Start Up Time <0.5
NO UV / IR	mA 95	%85 ENERGY Saving	25000h Lifetime
Hg 0,0mg	Optimally	105°	-10°C 40°C
Warm Up %60 < 0.5 s.	PF >0.5 Power Factor		

Features

- Low power consumption
- Efficient replacement for incandescent lamps
- Mercury free, no UV and IR radiation
- Instant on, 100% light output

LED 25000 Hours	GLS 1000 Hours
6W	48W

SMD LED **6V** YEARS GUARANTEE        **GU5.3**