



▶ LZ1*25/6



▶ LZ1*35/16 wyk.11



▶ LZ1*35/16 wyk.12




Nr kat. kolor	25 [□] / 4x10 [□]	35 [□] / 4x16 [□]	25 [□] / 4x16 [□]
Szary ●	84 101 002	84 104 002	84 115 002
Żółty ●	—	84 104 004	84 115 004
Napięcie izolacji	450 V	450 V	450 V
Prąd znamionowy	57 A	101 A	101 A
Wymiary (A/B/C)	37 mm / 56 mm / 36 mm	42 mm / 43 mm / 50 mm	42 mm / 50 mm / 50 mm
Ilość x przekrój znamionowy			
Drut Linka	1 x (6 ... 25 mm ²); 4 x (0.75 ... 10 mm ²) 1 x (6 ... 16 mm ²); 4 x (0.75 ... 6 mm ²)	1 x (6 ... 35 mm ²); 4 x (2.5 ... 16 mm ²) 1 x (6 ... 25 mm ²); 4 x (2.5 ... 10 mm ²)	1 x (6 ... 25 mm ²); 4 x (0.75 ... 10 mm ²) 1 x (6 ... 16 mm ²); 4 x (0.75 ... 6 mm ²)
Mocowanie	do podłoża	do podłoża	do podłoża
Opakownia zbiorcza	10 szt.	20 szt.	20 szt.

▶ LZ1*35/16 wyk.21




▶ LZ1*35/16 wyk.22



▶ LZ1*70/16




Nr kat. kolor	35 [□] / 4x10 [□]	35 [□] / 4x16 [□]	70 [□] / 4x16 [□]
Szary ●	84 049 002 ●	84 116 002 ●	84 057 002 ●
Żółty ●	84 049 004 ●	84 116 004 ●	—
Napięcie izolacji	450 V	450 V	630 V
Prąd znamionowy	101 A	101 A	172 A
Wymiary (A/B/C)	42 mm / 66 mm / 50 mm	42 mm / 43 mm / 50 mm	52 mm / 81 mm / 56 mm
Ilość x przekrój znamionowy			
Drut Linka	1 x (6 ... 35 mm ²); 4 x (0.75 ... 10 mm ²) 1 x (6 ... 25 mm ²); 4 x (0.75 ... 6 mm ²)	2 x (6 ... 35 mm ²); 4 x (2.5 ... 16 mm ²) 2 x (6 ... 25 mm ²); 4 x (2.5 ... 10 mm ²)	1 x (16 ... 70 mm ²); 4 x (6 ... 16 mm ²) 1 x (16 ... 50 mm ²); 4 x (6 ... 10 mm ²)
Mocowanie	do szyny TS35, TS32	do szyny TS35, TS32	do podłoża
Opakownia zbiorcza	20 szt.	20 szt.	36 szt.



▶ LZ1*70/16P



▶ LZ1*95/35P



▶ LZ1*240/35/25



Nr kat. kolor	25 [□] / 4x10 [□]	35 [□] / 4x16 [□]	2x240 [□] , 11x35 [□] / 2x25 [□]
Szary ●	84 047 002 ●	84 063 002 ●	84 002 002 ●
Niebieski ●	84 047 003 ●	84 063 003 ●	—
Żółto-zielony ●	84 047 009 ●	84 063 009 ●	—
Napięcie izolacji	630 V	630 V	690 V
Napięcie znamionowe	—	—	269 A
Prąd znamionowy	172 A	232 A	—
Wymiary (A/B/C)	52 mm / 81 mm / 58 mm	65 mm / 81 mm / 53 mm	84 mm / 80 mm / 145 mm
Ilość x przekrój znamionowy			
Drut Linka	1 x (16 ... 70 mm ²); 4 x (6 ... 16 mm ²) 1 x (16 ... 50 mm ²); 4 x (6 ... 10 mm ²)	2 x (25 ... 95 mm ²); 4 x (4 ... 35 mm ²) 2 x (6 ... 95 mm ²); 4 x (4 ... 35 mm ²)	
Mocowanie	do podłoża i na szynę TS35	do podłoża i na szynę TS35, z otworem do plombowania	bezpośrednio do podłoża
Opakownia zbiorcza	36 szt.	18 szt.	1 szt.
Informacje dodatkowe			Wej: zacisk typu V: 35-240 mm ² v-klemme; Wyj: 1x16...35/2x10...25 mm ² oczkowy