

**TECHNICAL DATASHEET**

**Egger DESIGN+**

Coreboard		UWF® - Ultra Wood Fibre
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		no
Class of use	<b>33</b>	
European Norm		
Format	Large	Large
Dimension mm (length x width)	1295 x 243	1295 x 243
Complete thickness	5	5
Integrated underlay	-	-
Bevel	WV4	WV4+2
<b>Packaging</b>		
Pallet	<b>Einwegpalette</b>	
<b>Paket information</b>		
	Piece	8
	m <sup>2</sup>	2,52
	kg	11,00
<b>Pallet information</b>		
	Piece	528
	m <sup>2</sup>	166,15
	kg	825,00
test methode	Classification and general requirements	
abrasion resistance (testA) according EN 13329, annex E	AC5 (IP ≥ 2000)	
abrasion resistance (testB) according prEN 15468, annex E	AC5 (IP ≥ 6000)	
impact resistance according EN16511	≥ 800 mm	
Micro scratch resistance according to EN16094	≤MSR-A2 ≤MSR-B2	
Effect of a castor chair according EN425	> 3000 cycles	
Castor chairs according EN16511	No damage shall be visible, when tested with foot Type 0 artefact	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according EN16511	≤ 20 %	
bonding strength [kN/m] according ISO 24334	length side > 1,0 narrow side > 1,0	
tolerance of top layer according EN16511	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Dimensional changes due to temperature changes according ISO 23999	< 0,25%	
Static indentation by constant pressure according EN16511	≤ 0,2 mm	

