LED MR16 GRID

Features:

- Ceramic heat sink design
- 85% energy saving
- 50/35W halogen lamp equivalent
- Switching power supply
- CE and RoHS compliant

Cautions:

- Non-Dimmable
- Power off before replacement
- Don't touch the lamp when lighting
- Don't use it in sealed fixture
- Consult competent electricians for technical support

Part No.	MR16 WF12P5	MR16 WF16P6
Comparable Halogen Wattage (W)	35	50
Wattage (W)	5	6
Lumens (lm)	350	450
Luminous Intensity (cd)	120	140
Beam Angle(deg)	105	105
CCT (K)	3000	3000
CRI (Ra)	>80	>80
Energy Efficiency Classes	A+	A+
Dimmable	No	No
Voltage (V)	ADC12	ADC12
Frequency(Hz)	50/60	50/60
Current (mA)	360	770
Socket	GU5.3	GU5.3
Lifespan(hrs)	25000	25000
Working Temperature (°C)	-20~40	-20~40
Storage Temperature (°C)	-20~85	-20~85
Weight	50	50
Mechanical Drawing		
Photometric Diagrams		







* Note: Data is subject to change without prior notice. Please visit www.civilight.com for further information.
* 2700K/4000K/5000K/6000K available

Applications:

- Hotels, bars, other residential buildings
- Museum, mall, restaurants, cafe