

SHINDENGEN

General Purpose Rectifiers

SIL Bridges

D10XB80

800V 10A

FEATURES

- Thin Single In-Line Package
- High current capacity with Small Package
- High IFSM
- Superior Thermal Conductivity


APPLICATION

- Switching power supply
- Home Appliances, Office Equipment
- Factory Automation, Inverter

OUTLINEDIMENSIONS

Case : 3S

Unit : mm



RATINGS

- Absolute Maximum Ratings (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-40~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		800	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load With heatsink Tc=100°C	10	A
		50Hz sine wave, R-load Without heatsink Ta=25°C	2.7	
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1cycle peak value, Tj=25°C	120	A
Current Squared Time	I ² t	1ms≤t<10ms Ti=25°C	60	A ² s
Dielectric Strength	Vdis	Terminals to case, AC 1 minute	2.5	kV
Mounting Torque	TOR	Recommended torque 0.5N·m)	0.8	N·m

- Electrical Characteristics (If not specified Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V_F	$I_F=5A$, Pulse measurement, Rating of per diode	Max.1.1	V
Reverse Current	I_R	$V_R=V_{RM}$, Pulse measurement, Rating of per diode	Max.10	μA
Thermal Resistance	θ_{jc}	junction to case With heatsink	Max.2.3	$^{\circ}C/W$
	θ_{jl}	junction to lead Without heatsink	Max.6	
	θ_{ja}	junction to ambient Without heatsink	Max.26	


D10XBx

Forward Voltage



D10XBx

Forward Power Dissipation




$T_j = 150^{\circ}\text{C}$

Sine wave

D10XBx


Derating Curve



Sine wave
R-load
with heatsink

D10XBx

Derating Curve



D10XBx

Peak Surge Forward Capability

