




Dual Enhancement Mode Field Effect Transistor (N and P Channel)

PRODUCT SUMMARY (N-Channel)		
V _{DSS}	I _D	R _{DS(ON)} (m Ω) Max
30V	18A	22 @ V _{GS} = 10V
		34 @ V _{GS} = 4.5V

PRODUCT SUMMARY (P-Channel)		
V _{DSS}	I _D	R _{DS(ON)} (m Ω) Max
-30V	-14A	34 @ V _{GS} = -10V
		54 @ V _{GS} = -4.5V



ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter		Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage		V _{DS}	30	-30	V
Gate-Source Voltage		V _{GS}	±20	±20	V
Drain Current-Continuous @ T _c	25°C	I _D	18	-14	A
	70°C		15	-12	A
-Pulsed ^a		I _{DM}	50	-50	A
Drain-Source Diode Forward Current		I _S	10	-6	A
Maximum Power Dissipation	T _C = 25°C	P _D	11		W
	T _C = 70°C		7.7		
Operating Junction and S storage Temperature Range		T _J , T _{STG}	-55 to 175		°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Case	R θ_{JC}	13.6	°C/W
Thermal Resistance, Junction-to-Ambient	R θ_{JA}	120	°C/W

STU309DH

N-Channel ELECTRICAL CHARACTERISTICS (T_A = 25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V			1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±10	uA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	1	1.8	3	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =10A		16	22	m ohm
		V _{GS} =4.5V, I _D =8A		22	34	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} =5V, V _{GS} =4.5V	20			A
Forward Transconductance	g _{FS}	V _{DS} =10V, I _D =10A		15		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C _{ISS}	V _{DS} =15V, V _{GS} =0V f=1.0MHz		640		pF
Output Capacitance	C _{OSS}			180		pF
Reverse Transfer Capacitance	C _{RSS}			110		pF
Gate resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1.0MHz		0.5		ohm
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	t _{D(ON)}	V _{DD} =15V I _D =1A V _{GS} =10V R _{GEN} =6 ohm		13		ns
Rise Time	t _r			12		ns
Turn-Off Delay Time	t _{D(OFF)}			40		ns
Fall Time	t _f			7		ns
Total Gate Charge	Q _g	V _{DS} =15V, I _D =20A, V _{GS} =10V		13		nC
		V _{DS} =15V, I _D =20A, V _{GS} =4.5V		6.8		nC
Gate-Source Charge	Q _{gs}	V _{DS} =15V, I _D =20A V _{GS} =10V		1.5		nC
Gate-Drain Charge	Q _{gd}			3.5		nC

STU309DH

P-Channel ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V$			-1	μA
Gate-Body Leakage	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 10	μA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1	-1.9	-3	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=-10V, I_D=-6A$		27	34	m ohm
		$V_{GS}=-4.5V, I_D=-4A$		43	54	m ohm
On-State Drain Current	$I_{D(ON)}$	$V_{DS}=-5V, V_{GS}=-10V$	-20			A
Forward Transconductance	g_{FS}	$V_{DS}=-10V, I_D=-6A$		10		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C_{ISS}	$V_{DS}=-15V, V_{GS}=0V$ $f=1.0MHz$		850		pF
Output Capacitance	C_{OSS}			220		pF
Reverse Transfer Capacitance	C_{RSS}			130		pF
Gate resistance	R_g	$V_{GS}=0V, V_{DS}=0V, f=1.0MHz$		4		ohm
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	$t_{D(ON)}$	$V_{DD}=-15V$ $I_D=-1A$ $V_{GS}=-10V$ $R_{GEN}=6\text{ ohm}$		12		ns
Rise Time	t_r			15		ns
Turn-Off Delay Time	$t_{D(OFF)}$			75		ns
Fall Time	t_f			35		ns
Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-20A, V_{GS}=-10V$		16		nC
		$V_{DS}=-15V, I_D=-20A, V_{GS}=-4.5V$		8		nC
Gate-Source Charge	Q_{gs}	$V_{DS}=-15V, I_D=-20A$ $V_{GS}=-10V$		1.6		nC
Gate-Drain Charge	Q_{gd}			4.7		nC

STU309DH

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}, I_S = 10\text{A}$	N-Ch	0.9	1.3	V
		$V_{GS} = 0\text{V}, I_S = -6\text{A}$	P-Ch	-0.9	-1.3	

Notes

a. Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2\%$.

b. Guaranteed by design, not subject to production testing.

N-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU309DH




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU309DH




Figure 10. Capacitance




Figure 11. Gate Charge




Figure 12. switching characteristics




Figure 13. Maximum Safe Operating Area




Figure 14. Normalized Thermal Transient Impedance Curve

STU309DH

P-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU309DH




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU309DH




Figure 10. Capacitance




Figure 11. Gate Charge




Figure 12. switching characteristics




Figure 13. Maximum Safe Operating Area





Figure 14. Normalized Thermal Transient Impedance Curve

STU309DH

PACKAGE OUTLINE DIMENSIONS

TO-252-4L




REF .	Millimeters	
	MIN	MAX
A	6.40	6.80
B	5.2	5.50
C	6.80	10.20
D	2.20	3.00
P	1.27 REF.	
S	0.50	0.80
G	0.40	0.60
H	2.20	2.40
J	0.45	0.60
K	0	0.15
L	0.90	1.50
M	5.40	5.80

STU309DH




TO-252-4L Tape and Reel Data

TO-252-4L Carrier Tape



symbol	A_0	B_0	K_0	P_0	P_1	P_2	T
Spec	6.96 ± 0.1	10.49 ± 0.1	2.79 ± 0.1	4.0 ± 0.1	8.0 ± 0.10	2.0 ± 0.05	0.33 ± 0.013
symbol	E	F	D_0	D_1	W	$10P_0$	
Spec	1.75 ± 0.1	7.5 ± 0.05	1.55 ± 0.05	1.5 ± 0.25	16.0 ± 0.3	40.0 ± 0.2	

TO-252-4L Reel



UNIT:mm

Width of carrier tape	8	12	16	24	32	44	56
$A \pm 0.1$	9.4	13.4	17.4	25.4	33.4	45.4	57.4
B	2.3	2.3	2.3	2.3	2.3	2.3	2.3
ϕC	100	100	100	100	100	100	100