

18300 DOUBLE SIDE EXHIBITION TAPE

Technical Data Sheet

Product description

18300 double sided exhibition tape is designed for bonding with removability functions. This tape can be used on almost every type of flooring, such as hard wood surfaces, stone, etc.

Construction

- Adhesive open side	Acrylic dispersion
- Adhesive covered side	Hot melt
- Carrier	Fbric
	White
- Liner	Paper
	White

Applications

- Suitable for most types of carpets
- Designed for carpet decorating, jointing and fixing

Technical details

Thickness	0,23 mm
Adhesive strength open side	7 N/25 mm
Adhesive strength covered side	30 N/25 mm
Shear adhesion	1000 g/625 mm ²
Service temperature range	-30°C to +80°C
Condensation water resistance	High
Aging resistance	Limited
Plasticizer resistance	Limited

Recommendations for use

Temperature: between +10°C and +30°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_10122015 Version 01

