

17350 REMOVABLE TAPE

Technical Data Sheet

Product description

17350 double coated tape with foil carrier can be used for a wide variety of applications, especially for removable bonds. This multipurpose tape may be used as a mounting aid for industrial applications, for renovation projects, during events and for trade shows. Commonly used carpet base can be applied to most flooring surfaces, good removability is ensured. This product is not approved for applications on premium stone and premium hard wood surfaces, as visible alterations to surface finish may occur.

Construction

- Adhesive	Open side: rubber, high tack Inner side: acrylic, low tack
- Carrier	Polyester foil
- Liner	Transparent Siliconized paper White

Applications

- Suitable for temporary applications during promotional events or exhibitions
- Can also be used for house hold purposes.
- Fixing point of display materials, print finishing and general applications

Technical details

Thickness	0,17 mm
Adhesive strength, open side	20,0 N/25 mm
Adhesive strength, covered side	5,5 N/25 mm
Shear adhesion	1 kg/625mm ²
Service temperature range	-30°C to +80°C
Elongation	110%
Moisture resistance	High
Solvent resistance	High
Ageing resistance	High

Recommendations for use

Temperature: between +10°C and +30°C. Surface must be clean, dry and free from dust, grease or oil. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C. The removable side of the tape is the outer: first apply the tape to the floor, then remove the liner and apply the carpet.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.

Frankrijkstraat 8
9140 Temse - Belgium
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64
info@optiontapespecialties.com - www.optiontapespecialties.com
OTS_05022014 Version 03

