

Glucopon[®] 600 CSUP

® = Registered trademark of BASF

Nonionic surfactants for detergent and cleaner industry

Chemical character

Aqueous solution of alkyl polyglucosides based on natural, plant origin fatty alcohol C₁₂-C₁₄, free of preservatives.

PRD-No.*

30530876

* BASF's commercial product numbers.

Properties

Glucopon® 600 CSUP is a yellow, cloudy and viscous liquid at room temperature and tends to form sediment below 30 °C.

Glucopon®	Unit	600 CSUP
Physical form (23 °C)		liquid
Active matter (100%-water content)	%	approx. 53
Water content (EN 13267)	%	approx. 47
pH value (EN 1262, 20% in 15% IPA)		approx. 12
Density (DIN 51757, 40 °C)	g/cm ³	approx. 1.08
Pour Point (ISO 3016)	°C	approx. 5
Surface tension (EN 14370, 1 g/l in distilled water, 23 °C)*	mN/m	approx. 28
Wetting (EN 1772, distilled water, 23 °C, 2 g Soda ash/l)		
0.5 g/l	s	>300
1.0 g/l	s	approx. 100
2.0 g/l	s	approx. 45
Foam volume (EN 12728, pg. 1, 40 °C, 2 g/l water at hardness of 1.8 mmol Ca- ions/l, after 30 s)	cm ³	approx. 250

* Applying Harkins-Jordan correction

The above information is correct at the time of going to press. It does not necessarily form part of the product specification. A detailed product specification is available from your local BASF representative.

Solubility

Details on the solubility of Glucopon® 600 CSUP in various solvents are given in the table below (Solubility 10% at 23 °C).

	Glucopon® 600 CSUP
Distilled water	○
Potable water (2.7 mmol Ca ²⁺ -Ions/l)	○
Caustic msoda (5%)	○
Hydrochloric acid (5%)	-
Salt solution (5%)	-
Solvent naphtha	-
Ethanol, Isopropanol	-
Aromatic hydrocarbons	-

+ = clear solution


± = sparingly soluble (insoluble sediment)

- = insoluble (phase separation)

○ = forms an opaque soluble, homogeneous emulsion

Viscosity

The relationship between viscosity and temperature is always an important point to consider when Glucopon® 600 CSUP is stored or shipped. This is shown in the following graphic (mPa·s, Brookfield LVT):



Viscosity of Glucopon® 600 CSUP after addition of (23 °C, Brookfield LVT, all data in in mPa·s)

Water addition (%)	Viscosity
+10	15000
+20	13000
+30	12000
+40	10000
+50	8500
+60	5000
+70	3500
+80	1500
+90	250

Storage

- a) The storage temperature of Glucopon® 600 CSUP should not be allowed to exceed 50° C.
- b) Liquid that has solidified or that shows signs of sedimentation should be heated to max. 70° C and homogenized before it is processed. Please mix sufficiently prior to use.
- c) Drums that have solidified or that have begun to precipitate should be reconstituted by gentle heating, preferably in a heating cabinet. The temperature must not be allowed to exceed 60 °C (short time 70 °C). Please mix sufficiently prior to use. This also applies if drums are heated by external electrical elements. Internal electrical elements should not be used because of the localized anomalies in temperature that they cause.
- d) Glucopon® 600 CSUP must be blanketed with nitrogen if they are stored in heated tanks at approx. 50 °C to prevent it from coming into contact with air. Constant, gentle stirring helps to prevent it being discolored or damaged as a result of prolonged contact with electrical elements or external heating coils.

Materials

The following materials can be used for tanks and drums.

AISI 321 stainless steel (1.4541 resp. X6CrNiTi1810)

AISI 316 Ti stainless steel (1.4571 resp. X6CrNiMoTi17122)

- Seals have to be stable against aqueous alkali (e.g. Teflon, Teflon coated seals; Klingerit K-Sil C 4500)
- Recommended as feed pumps: Screw rod pumps or rotary piston pumps

Shelf life

Provided it is stored properly and drums are kept tightly sealed, Glucopon® 600 CSUP have a shelf life of at least two years in its original packaging.

Safety

We know of no ill effects that could have resulted from using Glucopon® 600 CSUP for the purpose for which it is intended and from processing it in accordance with current practices.

According to the experience that we have gained over many years and other information at our disposal, Glucopon® 600 CSUP does not exert harmful effects on health, provided it is used properly, due attention is given to the precautions necessary for handling chemicals, and the information and advice given in our Safety Data Sheets are observed.

Please refer to the latest Safety Data Sheet for detailed information on product safety.

Note

This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

April 2013