

NERINE EFE SAE 5W/30

FUEL ECONOMY ENGINE OIL

320102901

DYADE
LUBRICANTS



FUEL ECONOMY RATING



FUEL ECONOMY ENGINE OIL

This is a full synthetic engine oil that has been developed for the FORD group that have the Ford WSS-M2C-913-A/B specification and replaces the M2C-913-A/B specifications. This specification is mandatory for all FORD models from model year 2009 and higher. Also this product is needed when the vehicles are equipped with the 2.2 Duratorq engines. This engine oil has over 3% fuel saving properties and can also be used for vehicles that have older specifications with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford Ka (diesel and gasoline from 2009).

Product information

“People buy this product because they have a FORD vehicle after 2009 that needs the FORD WSS-M2C-913-A/B specification.”

CATEGORY

Passenger Car Engine Oil

FINAL BASE OIL

Full Synthetic

AVAILABLE GRADE

SAE 0W/20
SAE 0W/30
SAE 5W/30

SPECIFICATIONS

ACEA A1/B1
ACEA A5/B5
API SL/CF
FORD WSS-M2C913-C
FORD WSS-M2C913-D
RENAULT RN 0700

AVAILABLE PACKAGING

1L
4L
5L
20L
60L
205L
1000L

PRODUCT SPECIFICATIONS NERINE EFE SAE 5W/30

TEST	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0.852
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	55
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	9.95
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	1.09
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	4200
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only

201901V01



DYADE MAINTAIN THE THINGS WE VALUE

DYADE LUBRICANTS B.V.
TYPOGRAAF 16 | 6921 VB DUIVEN
THE NETHERLANDS

0031 (0) 316 745 745
INFO@DYADE-LUBRICANTS.COM
WWW.DYADEGLOBAL.COM