Product data sheet Characteristics

EVH2S22P0CK

EVlink Wallbox - 22 kW - T2 attached cable - charging station





Main

		6
Range	EVlink	
Product name	EVlink Wallbox	Ť
Product or component type	Charging station	5
Device short name	EVH2	
Poles description	3P + N	
Mounting mode	Wall-mounted	in a second seco
Offer type	Standard	
Max power	22 kW 32 A	
Number of charge point	1	<u> </u>
Connection to the vehicle	Attached cable T2 4 m	E
Access control system	Key	

Complementary

Rated supply voltage	380415 V AC 50/60 Hz	
Earthing system	TN TT	 7 6
Number of inputs	1	
Input type	Contact for power limitation Contact for delayed charging	y d
Control type	white button, function: stop/restart Green button, function: cable unlocking	o co
Local signalling	1 multi-colour LED, function: status indication	
Height	480 mm	
Width	330 mm	
Depth	170 mm	
Product weight	7.5 kg	\. \.
Colour	Grey RAL 7016 White RAL 9003	
Standards	IEC 61851-1	

	IEC 61851-22 IEC 62196-1 IEC 62196-2
Product certifications	CE
	CB

Environment

IP degree of protection	IP54 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-3050 °C
Ambient air temperature for storage	-4080 °C
Relative humidity	595 %

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1514 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	