

RID 30 C-SERIES

DIESEL GENERATOR SET 30 KVA



POWER RATING

OUTPUT RATINGS		PRIME	STANDBY
Power	kVA kW	30 24	33 26,4
Current	A	43	47,3
Voltage	V	230 / 400	230 / 400
Frequency	Hz		50
Rated at power factor	cos φ		0,8

POWER RATING DESCRIPTION

Prime Rating

The ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

The ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

PRODUCT OVERVIEW

RATINGS DATA	
Order number Generator	713788
Alternator Model	Linz PRO18S C/4
Engine Type	IVECO - 80313AM1P
Generator type	synchronous
Protection class	IP 23
Control Panel	RID 1000 A

DIMENSIONS AND WEIGHTS

LENGTH (L)	WIDTH (W)	HEIGHT (H)	WEIGHT	TANK CAPACITY
1500 mm	752 mm	1160 mm	650 kg	150 l

NOISE LEVEL

1 METER	4 METER	7 METER	10 METER
86,5 dB(A)	83,5 dB(A)	81 dB(A)	80,5 dB(A)

RID 30 C-SERIES

DIESEL GENERATOR SET 30 KVA



ENGINE TECHNICAL DATA

ENGINE TECHNICAL DATA		PRIME	STANDBY
Engine output	kW	28,7	31,6
Engine type	IVECO - 80313AM1P		
Engine size	3-Cylinder; in-line		
Injection system	direct, mech injection pump		
Rotational-speed range	rpm	1500	
Bore Stroke	mm	104 115	
Cooling system	water + air		
Speed regulation	mechanical		
Compression ratio	17		
Displacement	l	2,9	
Weight with cooling system	kg	370	

FUEL SYSTEM

POWER STANDARD		25%	50%	75%	100%
Fuel consumption PRIME	l/h	-	3,8	5,4	7,1

EXHAUST SYSTEM

Silencer type	Industrial	
Max. exhaust back pressure	mbar	70
max. exhaust gas temperature	°C	525

AIR SYSTEM

Air Filter Type	replaceable Element	
Combustion air volume	m ³ /h	125
max. intake depression	mbar	25

COOLING SYSTEM

Cooling system	water + air	
Cooling system capacity	l	14
Max. coolant outlet temperature	°C	103
Cooling air flow	m ³ /h	1980

LUBRICATION SYSTEM

Oil type	RID 10W40	
Oil filter type	replaceable element	
Total oil volume	l	8,8
Max. oil temperature	°C	125

RID 30 C-SERIES

DIESEL GENERATOR SET 30 KVA



ALTERNATOR DATA

Alternator Model	Linz PRO18S C/4	
Generator type	synchronous	
Insulation Class	H	
Regulation Type	AVR	
Control System	self excited	
Execution	brushless	
Protection class	IP 23	
Stator Winding	Double layer with auxiliary winding	
Rotor Winding	I	with damping cage
Winding Pitch	2/3	
THD at full load	<3%	
Overspeed	rpm	2250
Air Flow Requirement	m ³ /h	414

ALTERNATOR PERFORMANCE DATA

VOLTAGE SERIES STAR, V	RATED POWER (125°C/40°C), KVA KW	X _d	X' _d	X'' _d
380 220	30 24	269 %	21,1 %	8,9 %
400 230	30 24	243 %	19,0 %	8,0 %
415 240	30 24	226 %	17,7 %	7,4 %
440 254	25 20	167 %	13,1 %	5,5 %

CERTIFICATIONS AND NORMS

EN60034-1	ISO8528-3	EN55011	Outdoor Noise Equipment Directive 2000/14/EC
-----------	-----------	---------	--

RID 30 C-SERIES

DIESEL GENERATOR SET 30 KVA



CONTROL PANEL

~ RID 1000 A ~

CONTROLLER FUNCTIONS

FUNCTIONS	RANGES, VALUES	
operating modes	automatic, manual, test and remote	available
mains control with limits	voltage, frequency, phase sequence	available
generator control with limits	voltage, frequency, power, phase sequence.	available
engine control with limits	start, stop, shutdown by alarms	available
power control	current, kW, kVA, kVA _r , power factor	available
statistic data mains	voltage, frequency and current	available
statistic data generator	voltage, frequency and current	available
fuel level control	in % and in liters	available
fuel consumption control and history	in l/h	available
working hours per day	in h	available
service hours	in h	available
battery service	in h	available
events log with time and date	255 events	available
alarm list programming	77 alarms	available
protocols	GSM, Ethernet, Modbus, Canbus, RID protocol	available

REMOTE MONITORING FUNCTIONS

mains voltage L1, L2, L3	in V, AC	available	engine temperature	in °C,	optional
generator voltage L1, L2, L3	in V, AC	available	environment temperature	in °C,	optional
genset battery voltage DC	in V, DC	available	generator run hours	in h,	available
mains power total	in kW,	available	generator maintenance hours	in h,	available
generator power total	in kW,	available	fuel level	in L,	available
mains frequency	in Hz	available	load on mains	indication	available
generator frequency	in Hz	available	load on generator	indication	available
current L1, L2, L3	in A,	available	mains supply	indication	available
power L1, L2, L3	in kW,	available	generator supply	indication	available

SPECIFIC ALARMS

GENSET DOOR OPEN	FUEL TANK OPEN	AIR FILTER CLOGGING	FIRE ALARM
optional	optional	optional	optional