



**BORMA WACHS®**

Wood Professional Cosmetics

## Technical data Sheet

REV 01 of 04.01.2016

# ZAPON INSULATOR PIGMENTED

## Special Gilding Insulator

### DESCRIPTION:

ZAPON INSULATOR PIGMENTED is a special sealer for gilding, to be applied on 2K Zapon Basecoat as adhesion promoter of any Borma gilding Goldsize for the correct application of imitation leaf.

Pigmented, it enhances the warmth and the depth of imitation leaf .

### CHEMICAL/PHYSICAL CHARACTERISTICS:

<b>Form:</b>	liquid
<b>Colour:</b>	See label
<b>Odour:</b>	typical
<b>Drying temperature:</b>	> 10°C
<b>Dilution:</b>	DNU – Universal Nitro Thinner
<b>Yield:</b>	20-30 m <sup>2</sup> /Lt

### HOW TO USE:

Shake well before use.

The product can be applied by brush but preferentially with airless spray-gun.

Suitable for intermediate application between basecoat and gilding glue.

Dilute 40-50% with DNU016, Universal Nitro Thinner, and then proceed with application, single coat, 30-50g/m<sup>2</sup>.

Wait minimum 4hrs for drying. The surface is then ready for following treatment with glue.

### STORAGE:

Store in a cool, well ventilated place, keep the container closed when not used. Keep away from heat, flames, sparks and other sources of ignition.

If well stored product is easily stable for over a year.

### PACKAGING:

The product comes in 500 mL, Lt. 1, Lt. 5 and Lt. 25 sized cans.

### WARNING:

Our technical sheets are compiled on the bases of results of our tests. Nevertheless our technical advice is given in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.