

Emkarate® RL 32-3MAF

Typical Properties Data Sheet



Description

Emkarate® RL 32-3MAF is an ISO VG 32 synthetic polyol ester (POE) lubricant formulated specifically for use in refrigeration and air-conditioning compressors using HFC refrigerants. This product provides effective wear protection for steel and aluminum surfaces for increased system life and improved efficiency and is suitable for both initial fill and service fill. The combination of low temperature characteristics and unparalleled chemical and thermal stability enable the use of **Emkarate® RL 32-3MAF** over a wide operating temperature range.

Analysis	Method	Typical Value
Viscosity @ 40°C (cSt)	ASTM D445	31.2
Viscosity @ 100°C (cSt)	ASTM D445	5.6
Viscosity Index	ASTM D2270	125
Pour Point (°C)	ASTM D97	-40
Density @ 20°C (g/ml)	ASTM D1298	0.981
Flash Point COC (°C)	ASTM D92	240
Acid Value (mg KOH/g)	ASTM D974	<0.05

*These values are not intended for use in preparing specifications. Additional technical information such as water content is available upon request.

CPI Fluid Engineering
www.cpifluideng.com



North and South America
The Lubrizol Corporation
2300 James Savage Road
Midland, MI 48642, USA

Telephone: 1 (989) 496-3780
Email: sales@cpifluideng.com

Europe, Middle East and Africa

Lubrizol Limited
Pavilion One, Belasis Court
Greenwood Road
Stockton-on-Tees
TS23 4AZ, UK

Telephone: +44 1642 565266
Email: euafricamesales@cpifluideng.com

Asia-Pacific

Lubrizol Southeast Asia (Pte) Ltd
44 Tanjung Penjuru
Singapore 609032

Telephone: + 65-66638 684
Email: asiasales@cpifluideng.com

