



Technical data Sheet

REV 00 of 20.10.2012

HOLZSPRAY

DESCRIPTION:

Fast drying nitro varnish special for wood.

Resistant to light and with extreme ease it allows a fast and efficient retouch on any external or internal wooden surface.

CHEMICAL/PHYSICAL CHARACHTERISTICS:

Appearance : liquid

Odour: characteristic

Colour :whitePH value :n.aDensity :1.1

Hydro solubility : not soluble **Flammability Point :** 23° C closed jar

Self Ignition Temperature : 340° C

HOW TO USE:

Fill in with BORMA HOLZMASSE any imperfections, therefore sandpaper and clean carefully the surface of any grease or dirt.

Shake well for a few minutes before using. If coloured, one advises to verify the colouring.

Spray lightly, crossing over a few times at about a distance of 25/30 cm approx.

Before any follow on work, wait 5/15 minutes depending on the amount used.

After using turn the spray up side down and spray to clean the nozzle.

STORAGE:

Keep the product away from flames, sparks or heat sources.

Avoid exposure to direct sunlight and do not expose the product to temperatures above 50°C. The storage space must be well ventilated and fresh.

PACKAGING:

The product comes in spray cans of 400ml.



WARNING:

The containers are pressurized.

Do not perforate or burn even after use.

Do not spray on naked flames or heated materials.

In areas that are not ventilated enough there is the possibility of a mixture of explosives. Keep out the reach of children.

Do not smoke.

Our technical sheets are complied on the bases of results of our tests. Nevertheless our technical advice is given in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.