### **DUCT FANS**





# **BDTX**

## AC CENTRIFUGAL IN LINE DUCT FANS Backward Curved

Straight airflow and easy installation - with the high pressure stability, low noise level and high efficiency. Both sides of the BDTX fans is suitable to fit into the centrifugal duct and can be fixed with fastening clamps. Fans can be performed in any mounting position.

### **Technical Drawings**





**MATERIAL**: The housing is made of electrostatic powder

coated sheet iron, impeller is made of galvanized sheet metal. Housing forming is proceeded by stamps for proper fit.

**INSULATION CLASS**: Class B, Class F

**DIRECTIVE** : EN 60335-1. EN 60335-2-80

**PROTECTION OF MOTOR:** Thermal overload protection is available upon

request. (Connector box- IP 55)

**SPEED CONTROL**: Speed can be adjusted using an optional

controller.

**APPLICATION AREAS**: For industrial and constructional applications,

in factories, hospitals, night clubs, offices, kitchens, bathrooms, theaters, condominiums,


restaurants, etc.



TYPE	Α	В	C1	C2	D	Е	F
BDTX 100	245	97	22	22	197	273	268
BDTX 125	245	122	20	20	188	273	268
BDTX 150B	272	147	23	25	192	286	295
BDTX 160A	272	157	23	25	192	286	295
BDTX 200A	330	196	30	28	230	380	352
BDTX 200B	330	196	30	28	230	380	352
BDTX 250A	330	247	30	28	227	380	352
BDTX 250B	330	247	30	28	227	380	352
BDTX 315A	400	313	30	30	285	415	422
BDTX 315B	400	313	30	30	285	415	422
BDTX 355	400	352	30	30	378	415	422

Dimensions are in (mm)

BDTX 355	BDTX 315-B	BDTX 315-A	BDTX 250-B	BDTX 250-A	BDTX 200-B	BDTX 200-A	BDTX 160-A	BDTX 150-B	BDTX 125	BDTX 100	TYPE	TYPE	
230	230	230	230	230	230	230	230	230	230	230	<	VOLTAGE	
50	50	50	50	50	50	50	50	50	50	50	Hz	FREQUENCY	
123	210	190	145	124	122	95	90	85	80	80	8	POWER	
0,63	1,1	0,9	0,63	0,56	0,55	0,43	0,4	0,38	0,36	0,3	(A)	CURRENT	
4	7	Δı	Ŋ	4	4	2,5	2,5	2,5	2,5	2	(μF)	CAPACITOR	
1420	2660	2560	2635	2500	2550	2280	2385	2425	2325	2610	d/d	SPEED	
1300	1750	1450	1150	1010	870	735	390	420	315	240	m³/h	AIR FLOW	
66	65	65	58	57	56	55	55	55	55	50	dB(A)	SOUND PRESSURE LEVEL	
9	6,9	6,8	5,3	4,9	4,8	4,4	ω	3,2	2,7	2,6	kg	WEIGHT	



180

60

80

160

240

320

400

480


Q (m³/h) Q (m³/s)


9-



300

BDTX 160-A







35

ACCESSORIES

SMOKE EXHAUST SYSTEMS

VENTILATORS

PLASTIC FANS

RADIAL FANS

AXIAL FANS

ROOF FANS

**DUCT FANS** 

### **DUCT FANS**

