

Technical Data Sheet REV 01 of 20.11.2015

# WATERBORNE PATINA

## Patina for aged, decapé, decorative effects

#### **DESCRIPTION:**

WATERBORNE PATINA is a professional product, mainly used t ogive an aged/decapé or decorative effect. Thanks to its special formulation the product can be easily applied on PU, acrylic, UV and lacquered basecoats. It's suitable for any wooden surface. Easy removal after drying.

#### **PHYSICAL-CHEMICAL CHARACTERISTICS:**

Form:	Thick liquid
Colour:	See label
Drying time (20°C):	15-20'
Dilution:	Water

#### HOW TO USE:

Mix well before use to grant the homogeneity of the material, that could sometimes stratify. Prepare WATERBORNE PATINA for use: dilute 10-30% with water, depending on your needs. On a pre-treated surface (one or more coats of basecoat, possibly protected with a transparent coat to get a more defined effect) apply the patina with a consumption of 30-50 g/sqm, single coat. After 20' tha patina is dried. Clean the surface with some steel wool or an abrasive pad to remove patina where needed and get an aged or decapé effect. Apply a transparent finish to protect the patina.

#### STORAGE:

The shelf life of the product is 12 months long from the date of manufacture, in its original packaging, tightly closed.

### PACKAGE:

The product comes in 250 ml, 1L, 5L, 20L sized cans.

#### WARNING:

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.

