



**BORMA WACHS**<sup>®</sup>

Wood Professional Cosmetics



## Technical Data Sheet

01 of 09.06.2017

# NATURAQUA BORMA SAUNA WACHS

Waxy protecting finish for sauna rooms  
Interior and Exterior Use - Waterbased

### DESCRIPTION:

Waterbased coating, based on high quality waxes and resins, specific for the protection of all interior wooden surfaces of sauna steam rooms (benches, panels, flooring, ceilings). Transparent, it does not alter the tone of the wood, giving a pleasant natural effect with dirt and water resistance. Tintable, it is available in standard trendy colours white, grey and black. Thanks to its low viscosity and permeability to water-vapour, the product is deeply absorbed by the wood keeping on the surface a natural silky touch.

The product is suitable also for exterior cladding; in this case an overcoating with Naturaqua Top Gel is recommended to improve the durability.

### PHYSICAL – CHEMICAL CHARACTERISTICS:

<b>Form:</b>	liquid
<b>Colour:</b>	Available: clear, white 60, grey 9002, black 60
<b>Odour:</b>	odourless
<b>Gloss level:</b>	30% satin matt
<b>Drying time:</b>	Dust free 1h, total drying in 24 hours
<b>Cleaning and Dilution:</b>	Water
<b>Yield:</b>	10-12 sqm/L

### METHOD OF USAGE:

To be applied on clean and dry surfaces, free from any residual of dust, grease and previous treatments, with following climate conditions: temperature >5°C, relative humidity < 80%.

Ready to use, paintbrush application is suggested (only paintbrush for the first coat), on clean and dry surfaces, in one or two coats. On outdoor surfaces apply at least two coats, with an interval of 8hrs between a coat and another. Total drying time:24hrs.

If necessary, lightly sand the surface before the second coat. Light resistant colours. Suitable also for spraygun application.

For thermotreated wood the coloured version is to be preferred to the clear one.

Pre-heat and ventilate the room before use.

**PACKAGE:**

The product comes in 375 mL, 750mL, 2.5Lt, 10Lt and 20Lt.

**STORAGE:**

Keep containers tightly closed, in a fresh, well ventilated area.

Do not stock near living flames, heat sources or sources of ignition. Protect the material from sunlight because it can accumulate electrostatic loads that can cause sparks.

Avoid contact with flames in the storing and usage of the product.

The product has a storage date of one year from the date it was manufactured.

**WARNING:**

Stir well before use.

If the product is applied in excess, the high content of waxes may turn the original colour grey and make the surface greasy.

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.