BORMA WACHS®
Wood Professional Cosmetics

Technical Data Sheet

00 del 20.10.2012

PARQUET WAX

Waterborne wax for parquet

DESCRIPTION:

For protecting and polishing vinyl, linoleum, rubber floors and lacquered wooden or cork floors. It forms a flexible glossy film, resistant and re-polishing with normal equipments, resistant to washing with usual neutral detergents for floors.

PHYSICAL – CHEMICAL CHARACTERISTICS:

Composition :	synthetic waxes and acrylic resin in water dispersion.
Colour :	colourless.
Cleaning :	whilst wet with water. Once dried it may be removed with Borma Universal Wax remover
Dilution :	ready to use product. For maintenance it may be diluted in the washing water of the floors.
Application :	with damp cotton cloth or with floor-polisher.
Coverage :	approx.15 ml/m ² depending on way of application.
Drying time :	approx. 1 hour.
Working temperature :	not lower than + 10 °C
Storage temperature :	not lower + 5 °C

HOW TO USE:

Clean thoroughly the resilient floor with a solution of Borma Universal Wax remover.
Rinse perfectly to remove all dirt residuals and let dry.
Apply with a damp cotton cloth or with the floor polisher, a thin and even coat of PARQUET WAX and let dry for approx. 1 hour, avoiding air draughts.
During application it is lightly perfumed.
If necessary, and depending on the porosity of the floor and on the protection to achieve, apply a second and a third coat, crossed, after complete drying in-between them.
After drying it forms a protective shiny film, hard and high traffic resistant, resistant to washing with normal neutral detergent for floors.
When more brightness is required, polish with polishing machine and polishing disc (WHITE).
It may be used as maintenance treatment on sealing treatments made with Bee's Holzwachs .
PARQUET WAX is particularly suited for maintenance of wooden floors lacquered with water based lacquers.
Cleaning of lacquered floors must be done with a cloth dampened with a neutral detergent for parquet in order to avoid damage of the lacquer and of the wood.

B.P.S. srl- Via E. Fermi, 17 - 30020 Torre di Mosto (Venezia) Italia.
Tel.: +39 0421 951900 Fax.: +39 0421 951902 www.bormawachs.it E.mail: info@bormawachs.it

BORMA WACHS®
Wood Professional Cosmetics

PERIODIC MAINTENANCE:
Clean or dust regularly the floor polished with PARQUET WAX, to remove dust and non-adhering dirt.
Wash the dirt floor with a normal neutral detergent for floors, then rinse with clean water and let dry.
Re-polish with polishing machine and use a WHITE polishing disc.
If necessary, apply a coat of PARQUET WAX where wear is more evident or on areas subject to heavy traffic.
The PARQUET WAX protective film may be refreshed while cleaning it using PARQUET WAX diluted 1:6 in cleaning water and polishing after drying.
To remove old films or too thick PARQUET WAX coats use Borma Universal Wax Remover.

PACKAGE:
The product comes in 1Lt plastic bottles in 12 pcs boxes and 5Lt plastic can in 02 pcs boxes.

STORAGE:
Store in a fresh, well ventilated place. Keep the container closed when not in use. Keep from freezing. The shelf life of the product is about 12months under good storage conditions.

WARNING:
Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.

B.P.S. srl- Via E. Fermi, 17 - 30020 Torre di Mosto (Venezia) Italia.
Tel.: +39 0421 951900 Fax.: +39 0421 951902 www.bormawachs.it E.mail: info@bormawachs.it