

























TECHNICAL CHARACTERISTICS

wineo 600				wineo	
Covering type according to EN ISO 10582: Heterogeneous resilient-flooring to glue					
	wineo 600 wood	wineo 600 wood XL	wineo 600 stone	wineo 600 stone XL	
Format	1200 x 180 mm	1505 x 235 mm	609,6 x 304.8 mm	900 x 450 mm	
Product thickness	2 mm	2 mm	2 mm	2 mm	
Planks, tiles / m² per box	18 / 3.89 m ²	12 / 4.24 m ²	18 / 3.34 m ²	12 / 4.86 m ²	
Boxes / m² per pallet	60 / 233.40 m ²	64 / 271.36 m ²	72 / 240.48 m ²	50 / 243.00 m ²	
Guarantee	20 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de				
Classification					Product composition
	Utilization class 23 Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices		1	Surface sealing
	Utilization class 32 Normal use in the commercial sector EN ISO 10874	Offices, boutiques, cafés		2	Surface texture various embossings
	Utilization class 41 Medium use in the light industrial sector EN ISO 10874	Workshop for precision mechanics		3	Wear layer Thickness 0.4 mm
	Wear layer binder content EN ISO 10582	Type I		4	Decor Decor film
	Wear resistance EN 660-2	Group T acc. to DIN EN 649:2011-05		5	Base layer
	Reaction to fire EN 13501-1	B _{fl} - s1		6	Backing
	Anti slip category DIN 51130	R 9			DESIGN FLOORING to glue 
	Slip resistance EN 13893	$\mu \geq 0.30$ - DS		Certifications	
	Anti-static properties EN 1815	≤ 2 kV		 windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32832 Augustdorf - 07 - Elastischer Bodenbelag DOP: 0401001 EN 14041:2004  Resilient Flooring to be used within a building.  ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A B C Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)  TÜV & Hearing Institute AG Schadstoffgeprüft Emissionsgeprüft PROFIL 78 730 4061-1  factory made coated 100% 	
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time			
	Light fastness EN ISO 105-B02	≥ 6			
	Residual indentation EN ISO 24343-1	~ 0.02 mm			
	Castor chair test EN 425 / ISO 4918	Type W – no visible change			
	Thermal resistance EN 12667	~ 0.01 (m ² K)/W			
	Impact sound reduction EN ISO 16251-1	~ 4 dB			
	Dimension stability EN ISO 23999	~ 0.15 %			
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203			

Relevant information:

- Installation in utilization class 41 possible (vehicular traffic excluded).
- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.