

130014 ED-S/DEDA

Field of application:

Industrial diesel engine
Brushless alternator with AVR regulation
Base frame with catch basin, fuel tank with electronic fuel Level Display
Aftersale-Service world wide



130014 ED-S/DEDA	985805
Cooling system	Water
Width	1090 mm
Length	2300 mm
Power factor cos (phi)	0,8
Voltage	400 / 230 V
Engine regulator	electronic
Frequency	50 Hz
Fuel Type	Diesel
Height	1800 mm
Number of cylinders	4
Engine oil quantity	17 l
Weight	1570 kg
Protection class alternator	IP 23
Torque-speed	1500 U min-1
Sound pressure level 7m	- dBA
Antifreeze quantity	19,7 l
Alternator type	Synchronous
Fuel capacity	520 l
Engine manufacturer	Deutz
Cubic capacity	4760 cm³
Consumption at 100% (PRP)	29,3 l/h
Consumption at 75%	21,7 l/h
Engine Type	BF4M1013FC
Variable Prime Power (PRP)	130
Starter	12 V
Consumption at 50%	14,9 l/h
Engine power (PRP/LTP)	117,6 / 124,0 kW
Consumption at 25%	8,7 l/h
Limited time power (LTP)	137 kVA
Air intake	Turbocharger

