

200014 ED-S/DEDA

Field of application:

Industrial diesel engine
 Brushless alternator with AVR Regulation
 Base frame with catch basin, fuel tank with electronic fuel Level Display
 Aftersale-Service world wide



200014 ED-S/DEDA	985809
Cooling system	Water
Width	1113 mm
Consumption at 50%	25,3 l/h
Consumption at 25%	13,1 l/h
Length	2655 mm
Power factor cos (phi)	0,8
Voltage	400 / 230 V
Engine regulator	electronic
Frequency	50 Hz
Fuel Type	Diesel
Height	1915 mm
Number of cylinders	6
Engine oli quantity	20 l
Weight	- kg
Protection class alternator	IP 23
Sound pressure level 7m	- dBA
Torque-speed	1500 U min-1
Antifreeze quantity	27,3 l
Alternator type	Synchronous
Fuel capacity	520 l
Engine manufacturer	Deutz
Cubic capacity	7150 cm ³
Consumption at 100% (PRP)	50,8 l/h
Consumption at 75%	37,7 l/h
Engine Type	BF6M1013FCG3
Variable Prime Power (PRP)	200
Starter	24 V
Engine power (PRP/LTP)	174,6 / - kW
Limited time power (LTP)	220 kVA
Air intake	Turbocharger

