

250014 ED-S/DEDA

Field of application:

Industrial diesel engine
Brushless alternator with AVR Regulation
Base frame with catch basin, fuel tank with electronic fuel Level display
Aftersale-Service world wide



250014 ED-S/DEDA	985811
Consumption at 100% (PRP)	49,9 l/h
Cooling system	Water
Width	1080 mm
Consumption at 50%	28,7 l/h
Consumption at 25%	14,6 l/h
Length	2700 mm
Power factor cos (phi)	0,8
Engine power (PRP/LTP)	215,4 / 238,4 kW
Voltage	400 / 230 V
Engine regulator	electronic
Frequency	50 Hz
Fuel Type	Diesel
Height	1900 mm
Number of cylinders	6
Engine oil quantity	26,5 l
Weight	2350 kg
Protection class alternator	IP 23
Sound pressure level 7m	- dBA
Torque-speed	1500 U min-1
Antifreeze quantity	27,3 l
Fuel capacity	520 l
Alternator type	Synchronous
Engine manufacturer	Deutz
Cubic capacity	7150 cm³
Consumption at 75%	39,9 l/h
Engine Type	TCD2013LO64V
Variable Prime Power (PRP)	250
Starter	24 V
Limited time power (LTP)	275 kVA
Air intake	Turbocharger

