

## Resichem 555 Resinox

*water based acrylic membrane top coat, UV Stable*

is a single component water based acrylic top coat. The coating can be applied to manually, mechanically, hydro-blasted and abrasive cleaned surfaces to provide long term corrosion protection

- Water based acrylic technology
- Single component
- Apply by brush, roller or standard airless spray
- Flexible with excellent elongation
- Touch dry in 60 minutes at 20°C
- Tolerant of less than ideal surface preparation
- No primer required on metallic surfaces
- UV stable
- Provides long term protection in C1-C5 corrosive environments



*Petrol storage tank at European refinery hydroblasted and coated with 2 x coats of Resichem 555 Resinox*



*Large crane at fertiliser plant required a long term corrosion protection system. All surfaces were mechanically abraded and coated with 2 x coats of Resichem 55 Resinox*





*Crude oil storage tank roof was cleaned with high pressure water at 1000psi. Resichem 555 Resinox was applied in 2 coats at 500 microns wet film thickness per coat.*

This material can be used to resurface and protect—

- **Bridges**
- **Stairways**
- **External tank surfaces**
- **Structural steel**
- **Containers**
- **Transformers**
- **Pylons**



*As part of a large coating contract 8 crude oil storage tanks were coated at a European oil refinery with Resichem 555 Resinox*

