



















TECHNICAL CHARACTERISTICS

wineo 400 Multi-Layer Long-lasting multi-layer floor (Multi-Layer) according to ISO 20326 for glueless installation			wineo	
	wineo 400 wood Multi-Layer	wineo 400 wood XL Multi-Layer	wineo 400 stone Multi-Layer	
Format	1222 x 182 mm	1520 x 230 mm	601 x 310 mm	
Product thickness	9 mm	9 mm	9 mm	
Planks, tiles / m² per box	9 / 2.00 m ²	6 / 2.10 m ²	9 / 1.68 m ²	
Boxes / m² per pallet	44 / 88.00 m ²	52 / 109.20 m ²	60 / 100.80 m ²	
Guarantee	15 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de			
Classification			Product composition	
	Utilization class 23 EN ISO 10874	Heavy-duty use in the domestic area		1 Surface sealing
	Utilization class 31 EN ISO 10874	Medium use in the commercial sector		2 Surface texture Various embossings
	Wear layer binder content EN ISO 10582	Type I		3 Wear layer Thickness 0.3 mm
	R9 Anti slip category DIN 51130	R 9		4 Decor Decor film
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time		5 Base layer
	Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6		6 Core board Aqua-Protect®
	Residual indentation EN ISO 24343-1	≤ 0.1 mm		7 Profile connection • LocTec® technology 
	Thermal resistance EN 12667	≤ 0.058 (m ² K)/W		8 Profile sealing
	Impact sound reduction EN ISO 16251-1	~ 14 dB		9 Insulation mat Sound-Protect Eco
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		wood XL registered embossed surface stone bevelled edge
<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="border: 1px solid black; padding: 10px; width: 30%;">  <p>Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf</p> <p>DOP: 0301010 EN 14041:2004 / AC2006 1658</p> <div style="display: flex; justify-content: space-around;">      </div> <p style="text-align: center;">www.wineo.de</p> </div> <div style="width: 30%; text-align: center;"> <p>ÉMISSIONS DANS L'AIR INTÉRIEUR*</p>  <p><small>Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)</small></p> </div> <div style="width: 30%; text-align: center;">  <p>factory made coated</p> </div> </div>				
Relevant information:				
<ul style="list-style-type: none"> Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C. Cleaning and care: see separate cleaning & care instruction. Technical subjects can be changed by Windmüller GmbH. 				

