

EMO12

Wall-mount air conditioners for outdoor applications

COOLING CAPACITY

1250 W




Accessories	
Pack of 5 fabric air filters	C15000163
Pack of 1 metal air filter	C15000164
External stainless-steel framework	
Coating in non-standard colour	
48VDC evaporator fan	
Anti-tamper screw kit	
High temperature alarm	
Pressure alarms (low, high)	

Features	UoM	EMO12BM1B	EMO12CM1B	EMO12GM1B
Cooling capacity EN14511 - A35A35	W	1250	1250	1250
Cooling capacity EN14511 - A35A50	W	910	910	910
Power supply	V ~ Hz	230 1~ 50-60	115 1~ 50-60	400/440 2~ 50-60
Width	mm	415	415	415
Height	mm	1109	1109	1109
Depth	mm	261	261	261
Max current	A	3.8	7.6	2.2
Inrush current	A	11	24	8.5
T Fuse	A	6	10	4
Power draw EN14511 - A35A35	W	680	690	690
Power draw EN14511 - A35A50	W	790	800	800
Operating cycle	-	100%	100%	100%
Electrical connection	-	4-pin plug	4-pin plug	4-pin plug
R134a Refrigerant	kg	0.26	0.26	0.26
Max refrigeration circuit pressure	bar	25	25	25
External air fan capacity	m ³ /h	860	860	860
Cabinet air fan capacity	m ³ /h	570	570	570
Internal temperature range	°C	+20 - +46	+20 - +46	+20 - +46
Temperature regulation	-	Electromechanical thermostat, factory set to 35°C		
External temperature range	°C	-20 - +55**	-20 - +50	-20 - +50
EN60529 ingress protection - cabinet side	-	IP55	IP55	IP55
EN60529 ingress protection - ambient side	-	IP34*	IP34*	IP34*
Noise level	dB (A)	65	65	65
Weight	kg	38	40	40
Colour	-	RAL 7035 embossed effect		
Conformity	-	CE	CE	CE

** 50 °C at 60 Hz

* IP54 rated exterior electrical connections

Performance



Dimensions

