



BORMA WACHS[®]
Wood Professional Cosmetics



Technical data Sheet

REV 00 of 20.10.2012

FIBER REINFORCED WOOD FILLER

DESCRIPTION:

Waterborne fiber made filler, formulated with high quality raw materials and reinforced with structural fibers of remarkable elasticity. Practically without withdrawal, it is particularly suitable for filling and smoothing wood. Among its main features are: good adhesion, excellent resistance to shrinkage, easy sanding, large filling capacity.

CHEMICAL/PHYSICAL CHARACTERISTICS:

Appearance:	Paste
Color:	Complies with color labeling
Odor:	Odorless
Density:	1.750 g / Lt
Dilution:	water-soluble (ready to use)
Drying:	6-8 hours with normal humidity. Paintable after 24 hours.
Filling capacity:	up to 15mm
Sanding:	Excellent
Withdrawal:	Crack damage: no withdrawal, up to 15mm depth Hole damage: very limited withdrawal, up to 15mm depth

HOW TO USE:

The product is ready for use, is applied with a spatula directly into imperfection and let dry for about 6/8 hours. Sand the excess then stain, overpaint or apply wax..

STORAGE:

Keep the containers tightly closed in warehouses at environmental temperature.

PACKAGING:

The product is packaged in jars of 250 gr. (125 ml), 500 gr. (250ml.), 01 Kg (500ml.), 05 Kg (2500 ml).

WARNING:

Our technical sheets are compiled on the bases of results of our tests. Nevertheless our technical advice is given in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.