



BORMA WACHS®

Wood Professional Cosmetics



Scheda Tecnica

REV 00 del 20.10.2012

BITUMINOUS BEESWAX

DESCRIPTION:

A professional product that collects in its blend the main mineral, animal and vegetal waxes. Bituminous wax for the antique effect on gilded surfaces, allows to carry out coatings of inimitable beauty. Based on pure beeswax and carnauba nourishes, regenerates, protects and polishes the treated surfaces.

PHYSICAL – CHEMICAL CHARACTERISTICS:

Appearance:	paste
Colour:	brown
Odour:	typical
Solubility:	- In common organic solvents: miscible - In water: immiscible
Specific Gravity:	0,82 Kg/Lt ± 0,03 (20°C)

HOW TO USE:

Before applying please make a preliminary test.
With a piece of wool or with the steel wool for furniture producers spread the wax evenly. After 1 or 2 hours, depending on the type of wood and the temperature of the environment, proceed to polishing, the more intense the more brilliant.

PACKAGE:

The product is packed in tins of 300 mL, 1 Lt, 25Lt.

STORAGE:

Store in a cool, well ventilated place, keeping the containers closed when not in use. Keep away from heat, open flames, sparks and other sources of ignition.

FOREWORD:

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.