



## Technical data Sheet

REV 00 of 20.10.2012

# SHELLAC SANDING SEALER

### DESCRIPTION:

Shellac Sanding Sealer is transparent shellac based, of the highest quality. Produced with natural shellac wax, and given its transparency, it is ideal as a first coat in the treatment of wax or shellac on light wood such as pine etc. Completely formulated with natural products, and ready to use, it is fast drying and of notably adhesion.

### CHEMICAL/PHYSICAL CHARACTERISTICS:

<b>Appearance:</b>	liquid
<b>Colour:</b>	colourless ( lightly golden)
<b>Odour:</b>	characteristic
<b>Dilution:</b>	ready to use
<b>Possible dilution :</b>	10 - 20 % ethylic alcohol
<b>Drying process:</b>	2 / 3 hrs at 20° C
<b>Dry residue:</b>	30 %
<b>Specific weight:</b>	0,83 + 0,03
<b>Yield:</b>	9 /12 mq x LT

### HOW TO USE:

Spread with the aid of a brush and wait until it is completely dry. After the first coat, a second application is advisable, after the surface is perfectly dried and lightly sandpapered, with a fine grain min. 240. After, preferentially two coats, the product allows a very easy brilliant result with wax polishes or shellac polishes.

### STORAGE:

The product must be stored, handled and used within the standards of hygiene and safety industrial practice

### PACKAGING:

The product is packed in cans of 500ml, 1 litre and 5 litres.

### WARNING:

Our data sheets are prepared on the basis of average results of our tests. However, our technical advice is given in good faith but without warranty. In fact, different supports, conditions of application systems, dilutions are determinant for the final result and often beyond any control. The user must test the product to see if suitable for his needs. We will ensure the continuity of the chemical - physical characteristics.