

* incl. 20 [-5; +30] mm pull out

3D model is available on request

Specifications

Max. working pressure	250 bar
Weight	116 kg
Working volume	30 L
Total volume	33 L
Max. cyl. load (start tipping)	345 kN

Max. pump flow

With KO ¹	220 L/min
Without KO ¹	162 L/min
With KO ¹ below -20°C	154 L/min
Without KO ¹ below -20°C	113 L/min

Tipping time

With KO ¹	8 sec
Without KO ¹	11 sec
With KO ¹ below -20°C	11 sec
Without KO ¹ below -20°C	16 sec
Allowable lowering time	7 sec

Extension	1	2	3	4	5	6	7	Total
Effective diameter [mm]	137	118	99					2675
Stroke* [mm]	875	900	900					

Technical notes

- This cylinder is a lifting device only.
- It should not be used as a structural member and should not be subjected to side loads.
- Tipping valve must have a pressure relief at the cylinder port set not higher than max. working pressure.
- Verify max. cyl. load.
- Working temperature range is between -40°C and +80°C.
- Max. duration of extension is 0.5 hours (excluded hard chromed stages).
- Cylinder is painted black (RAL9005) with a min. thickness conforming to the 480 hours neutral salt spray test as per ISO 9227.
- ¹ Hyva knock-off.


Related documentation

Bracket options: 015BRA13 & 015BRA17

Mounting instructions: CYL-0032

Oil specifications: OIL-0011
Spec sheet explanation: CYL-0041

Tipping weight




BL	body length
OH	rear overhang
Ycog	vert. pos. centre of gravity
Qo	pivot length
C	bracket length
At	tipping angle
	stroke x 60 / Qo

BL [mm]	3500			3450			3400		
OH [mm]	200	400	600	200	400	600	200	400	600
At [°]	47	50	54	48	51	55	48	52	56
Ycog [mm]									
400	56	64	76	56	65	78	57	66	80
700	64	77		65	79		66	81	
1000	76			78					

Tipping weight [ton] at maximum pressure of 250 bar for a vertically mounted cylinder and C is 158 mm

For detailed tipping calculations please refer to: <https://tipper.hyva.com>


Pos.	Part no.	Description	Qty.
C01	71839110	DUST COVER FE 129-3/137-3	1
P01	70473201	PISTON MN2 S 099-1130-HD-HC	1
P02	70207099 K	SLIDER MN 099 (2 x 1/2) A35	1
P03	70216099 K	OUTER STOPRING MN 099 A22	2
P04	70230099	BOTTOM PLATE PISTON MN 099 MK2 HD	1
P05	01745042 K	CIRCLIP 85 DIN 472 (90.5x3.0)	1
P06	70260215 K	O-RING PISTON BOTTOM 099	1
P07	70235401	PISTON EYE SPH. MN 099 MK2 L=075 GR	1
P08	70260115 K	O-RING 82.14 X 3.53 MM	1
P09	01770085 K	SPHERICAL BEARING D.50.3 DO GREASED	1
P10	01770560 K	CIRCLIP 75 DIN 472 (79.5x3.0)	1
P11	71875012	PIN ROUND HEAD GROOVED 8x15 mm	2
P12	56288044 K	GREASE NIPPLE M8x1 DIN 71412	1
P13	01317670 K	GREASER PROTECTION CAP	1



S21	70674200	STAGE MN2 118-1125-HD	1
S22	70202118 K	PACKSET MN 118 TANDEM SEAL	1
S23	70207118 K	SLIDER MN 118 (2 x 1/2) A35	1
S24	70216118 K	OUTER STOPRING MN 118 A22	2
S25	70217118 K	LIFTRING MN 118 A22	1

S11	70675200	STAGE MN2 137-1125-HD	1
S12	70202137 K	PACKSET MN 137 TANDEM SEAL	1
S13	70207137 K	SLIDER MN 137 A35	1
S14	70216137 K	OUTER STOPRING MN 137 A22	1
S15	70217137 K	LIFTRING MN 137 A22	1

B01	70376210	BASE MN2 E 157-1164-4/4NSAE-330-O219-HD	1
B02	70203157 K	PACKSET MN 157	1
B03	70225355	BOTTOM PLATE MN2 157	1
B04	70270157 K	SEAL BOTTOM PLATE MN 157	1
B05	70220157	LOCKING PLATE MN 157	3
B06	01732055 K	BOLT HEX M8X20X1.25 SET 6 PCS	1
B07	01732559 K	WASHER SPRING M8 SET 6 PCS	1
B08	01793061	EYE TRUNNION TUBE (63-52.5) L=219	1
B09	01746121 K	BOLT LOCKING M8x25 DIN 7991	1
B10	56288044 K	GREASE NIPPLE M8x1 DIN 71412	2
B11	01317670 K	GREASER PROTECTION CAP	2



Seal kit complete

	71907531 K	Consists of all packsets with packset grease and O-rings	
--	------------	--	--

Notes

The inner stopring is pre-mounted in the grooves on spare bases and stages. Therefore, when ordering new tubes, it is not required to order inner stoprings separately.