



## Scheda Tecnica

REV 00 del 20.10.2012

# TOP GEL TIXO HIGH SOLID

Wax finish for internal - external use, high density - prevents dripping, high solid

### DESCRIPTION:

Not-flaking finish based on natural waxes and resins. Thanks to the high content of dry solid residue, ensures a long-lasting protection especially for exterior wood and reduces the amount of solvent in the mixture. The precious substances contained in it combined with UV filters, prevent the formation of chromophores mold and prevent from insect attacks (like woodworms), providing excellent resistance to atmospheric agents. Its high density makes it easy to brush application, even on vertical. Ideal for wooden houses, siding, trusses, pergolas. It does not contain lindane and PCP.

### PHYSICAL/CHEMICAL CHARACTERISTICS:

<b>Appearance:</b>	liquid
<b>Color :</b>	colored
<b>Odor :</b>	characteristic
<b>Density:</b>	0,96 kg/Lt
<b>Solid content:</b>	62%
<b>Drying time 20-25° C:</b>	<ul style="list-style-type: none"><li>- Dust free: 3-5 hours</li><li>- Second Coat: 16 hours</li><li>- Dried in depth: 24 / 36 hours</li></ul>
<b>Working temperature:</b>	5 – 35 °C
<b>Yield:</b>	14 - 18 mq/Lt a depending on wood absorption
<b>Cleaning of tools:</b>	White spirit, Solvoil 04 or Solvoil Plus
<b>Covering duration:</b>	3 years, depending on the intensity of the weather



**BORMA WACHS**<sup>®</sup>

Wood Professional Cosmetics

**HOW TO USE:**

Clean residual from old wasted paint, degrease and sand the surface to be treated. On a dry and intact surface, apply the first coat of TOP GEL TIXO HS with a brush (recommended). For an application for interior only first-hand is required, for external application apply at least two coats instead, if necessary separated by sanding.

The finished support will arrive at the final gloss level once completely dry, after 24/36h. It is possible to color TOP GEL TIXO HS with Oil-based Pigmented Pastes of Borma Wachs range. Good color retention over time.

For maintenance, it is recommended to paint over a clear finish like TIXO TOP GEL.

**STORAGE:**

Store in a cool, well ventilated place, keeping the containers closed when not in use. Keep away from heat, open flames, sparks and other sources of ignition. The storage period shall be 12 months from date of manufacture in original packaging.

**PACKAGING:**

The product is packed in tins of 375 mL, 750 mL, and 2.5 Lt.

**WARNING:**

Sawdust, cotton cloth, paper and similar products soaked with liquid product and let in such condition may cause spontaneous combustion. Therefore, in case of presence of these materials for cleaning, ensure adequate air ventilation of the rooms in order to allow a rapid drying of the product or wet them with water before disposal.

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.