

TAG Chemicals GmbH

An der Steinlach 15, 65474 Bischofsheim, Germany

Tel.+49 (0) 6144-3351-0, Fax +49 (0) 6144-3351-11, email:info@tag-chemicals.com

Technical Information

Release Agent TM- 828 conc. 35%

Release Agent TM-828 conc. 35% is a water-based release system designed for moulding operations when high temperature stability, high degree of slip, and abrasion resistance of the release film are important.

Release Agent TM-828 conc. 35% is water thin liquid and ready to use. The release film is micro thin and stable until 260°C..

Release Agent TM-828 conc. 35% reduces build-up on moulds when applied according to instructions.

Properties:

Colour: white
Density: 1,0 g/cm³
Self life: 12 months

Application Field:

Rubber, all kind of rubber-types and rubber moulding.

Instructions:

Release Agent TM-828 conc. 35% can be diluted 1:10 – 1:20 with demineralised water

Advantages:

1. Water based
2. Easy to apply
3. Excellent release properties
4. Prevents build up on the moulds
5. Universal for all rubber-types
6. High dilution

Application:

Thoroughly clean the mould. Afterwards apply **Release Agent TM-828 conc. 35%**.

Apply at least two uniform, thin coats before it goes to production. Allow a short drying time.

Reapply a light coat of **Release Agent TM-828 conc. 35%** at process temperature when required, to maintain desired release.

Further Information:

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.