

Product quality				
<b>Formats</b>		853 x 400 x 8 mm	1285 x 194 x 8 mm	2200 x 235 x 8 mm
<b>Packaging</b>	<b>Pack:</b>	5 elements / 1.706 m <sup>2</sup> / 12,05 kg	10 elements / 2,,493 m <sup>2</sup> / 16,69 kg	6 elements / 3.102 m <sup>2</sup> / 20.87 kg
	<b>Pallet:</b>	57 packs / 97.24 m <sup>2</sup> / 701,85 kg	40 packs / 99,72 m <sup>2</sup> / 682,49 kg	39 packs / 120.98 m <sup>2</sup> / 843.76 kg

Tolerances (Requirement EN 16511:2014+A1:2019)		
<b>Squareness of the elements (≤ 0.50mm)</b>		≤ 0,15 mm
<b>Determination of Linearity (≤ 0.30 mm/m)</b>		≤ 0,20 mm/m
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50 / ≤ 1.0 %)</b>	≤ 0,35/≤ 1,0 %
	<b>wide (≤ 0.10 / ≤ 0.15 %)</b>	≤ 0,10/≤ 0,15 %
<b>Surface flushness</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.10 mm)
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.15 mm)
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.05 mm)
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.10 mm)





















Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (up to max. 20sqm)
Lifetime	10 Years	- cleaning an maintenance see instructions
		- technical changes reserved









Classification		
	Test method	Rating
 <b>Utility class 23</b> domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
 <b>Utility class 33</b> commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
 Reaction to fire	EN 13501-1	C <sub>f</sub> s1
 Slip resistance	EN 13893 EN 14041	μ ≥ 0,50 DS
 Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
 Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	EN 425	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,075 m <sup>2</sup> *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
 <b>E1</b> Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	≤ 0,05 ppm
 Acoustical - Impact noise reduction	EN ISO 10140	16 dB (on PE film) 17 dB (on Akustik-Protect 100)
 Length- and Square separating force	ISO 24334	lengthwise ≥ 6 KN/m transversely ≥ 4 KN/m
 Abrasion	prEN 15468 Annex A	> 7.000 rev.
 Impact resistance	EN 13329 Annex F	≥ 1.800 mm
 Dimensional stability	EN 16511	≤ 0,25 %
 Micro scratch resistance	EN 16094	Method A MSR-A2 Method B MSR-B1
 Slip resistance on an inclined plane	DIN 51130	Wood texture: R10 / Other: R9
 Disposal	EAK-Code-number	17 09 04
 Suitable for damp rooms: With up to four hours of protection in the case of standing water (please observe installation instructions).		

Changed:	QMB Parador	File:	20191001_PA_TDS_Modular-ONE_EN
Date:		Latest update at:	<a href="http://www.parador.eu/service/catalogues-downloads/technical-data-sheets">www.parador.eu/service/catalogues-downloads/technical-data-sheets</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.10.2019