



Technical Data Sheet

00 del 20.10.2012

HOLZWACHS

DESCRIPTION:

A professional product containing the main waxes of mineral, animal and vegetable origin, preventing the formation of cracks, swellings or fading of all types of wood surfaces.

Its protective capacity is sustained by extra resistant luminous pigments which enhance the warmth and colour of the wood, retouching possible flaws. Can be applied with a brush or a piece of woolen cloth. Wait a few minutes before polishing.

Contains virgin bees' wax and carnauba.

ANTI - WOODWORM

Colors available: neutral, yellow, light walnut, medium walnut, dark walnut, mahogany.

PHYSICAL - CHEMICAL CHARACTERISTICS:

Physical state: 20°C paste

Density: 0.7730 20°C pycnometer

Melting point: 45% pH value: 7.6

Yield: 0.5 Lt. 35 sq.m.

PACKAGE:

Available in 500 ml, 1LT and 5LT cans.

STORAGE:

Keep the material in a clean, well ventilated place, away from heat resources and direct sunlight, possible between a minimal temperature of 5° C and a maximum of 35° C.

The product should be keep preferably in original containers.

WARNING:

Our technical data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.