

BLUE WAYUP PRODUCT SHEET



Description :

- Frame made in steel
 - Laser cutting and bending sheet metal, tubes and profiles
 - Epoxy baked painting
 - Ball bearing castors
 - Total weight : 29 kg
 - Weight capacity : 150 kg
 - Lifespan : 8 years (except electrical parts)
- Medical products (93/42 EEC amended by 2007/47/EEC)
 - Electromagnetic compatibility (2004/108/EC)
 - Applicable standards :
 - BS EN 60601-1 : 2007
 - BS EN 60601-1-2 : 2007
 - BS EN ISO 10535 : 2007
 - DC motor low voltage 24V
 - 24V / 120VA power
 - Maximum strength : 8000 N
 - Electronic protection when overloaded
 - Protection class : II
 - Protection type : IPX 4
 - Stop limit switch
 - Box in ABS
 - Handcontrol with spiral cable, low voltage 24V
 - Protection against overloading through thermo-switch
 - Loudness : less than 55dB at a distance of 1 meter.

Motorization Technicals Characteristics :

- Removable battery pack
- Digital display of the autonomy
- Power cord
- Emergency stop button
- Remote control 2 functions protection class IPX4
- Electrical security lowering system
- Wall charger (in option)

Dimensionals Characteristics :

- A. Total length: 94 cm
- B. Minimum lifting height: 79 cm
- C. Maximum lifting height: 123 cm
- D. Total height: 95 cm
- E. Frame height: 8 cm
- F. Minimum base width: 29,5 cm
- G. Maximum base width: 59 cm
- H. Turning diameter: 90 cm

