



Max. pressure: 350 bar
Max. flow: 40 l/min

PRESSURE SETTINGS
350 bar 5 l/min
Adj. pressure range: 100-350 bar
pressure increase 100 bar/turn
Pilot ratio: 3.6 : 1

Port size:
V2, C2 = ϕ 8 (3/8)
Pil = ϕ 5

Manifold: aluminium

Seal: BUNA N-70 SHORE.

For dimensions without tolerance, consider ± 0.5 mm

All dimensions : mm

Denominazione / Denomination

VBSO-SE-FC-NA-38-1.3-35C

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Specifications

Valve modified

Hex. 5

Hex. 17

65 max.

O-Ring ϕ 15.08x2.62

ϕ 14
Pil

ϕ 20
V2

ϕ 20
C2

O-Ring ϕ 9.19x2.62

9

63,5

27

40

16

85,5

50

25,5

Massa / Mass (kg) 1,000

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Richiesta / Request UT11950

Rexroth
Bosch Group

Bosch Rexroth Oil Control S.p.A.

Ufficio Tecnico

Technical Dept.

Gerarchia Prodotto

Product Hierarchy

Kit guarniz.

Seal kit

Modifiche

Changes

Sostituisce il

Replaces

Codice

Code

Material number

Rev. 01 del 15/12/09