



Technical data Sheet

REV 00 of 20.10.2012

HOLZ ANTIX 2008

Special waterborne stain binder

DESCRIPTION:

Holz Antix 2008 is a waterborne ready-to-use vehicle, with a special aging effect. If applied on tannin-rich woods, e.g. oak, it allows to easily create old-looking wooden supports. If added with the waterborne pastes (cod. COW00xxx) included in the Coloroil System, it allows to obtain special colour effects on woods such as larch.

CHEMICAL/PHYSICAL CHARACTERISTICS:

Form:	liquid
Colour:	clear (to be coloured with Borma waterborne pastes)
Odour:	odourless
pH:	11
Dilution and cleaning:	water

HOW TO USE:

Apply directly by brush or by spray on the wood surface. Then let it act for 6/8 h, and wait until the surface is completely dry. Finally proceed with sanding (220/240 grain) and then overpaint or treat the surface with oil. Before any finishing with Borma oils and waxes, make sure that the surface is completely dry.

Pay attention that while Holz Antix 2008 is acting, the look of the treated surface will change a lot.

Moreover the result will be different when working with different kinds of wood; this is because the product simulates exactly the natural process of aging in time.

STORAGE:

Store in a cool, well ventilated place, keep the container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition.

Keep from freezing.

PACKAGING:

The product comes in 1 Lt, 5 Lt, 15 and 120 Lt sized containers.

WARNING:

Our data sheets are prepared on the basis of average performance of our tests.

However, our technical advices are given in good faith but without any warranty.

In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs.

We will ensure the continuity of the chemical-physical properties.