

## FLEXEM——IIoT HMI FE6000 Series

### Model: FE6100CE

#### Overview

Flexem Industrial HMI 6000 Series, a new generation of IIoT human-machine interface. It is high-quality and cost-effective touch screen, industrial ABS plastic shell, low cost, high reliability.

The mainboard is treated with a special coating (three anti-paint) to adapt to harsh environments.

The new model opens with a more practical down-line approach, and the redesigned front face has a better looking look, and higher resolution model is available.

By selecting the Flink IIoT module, you can upgrade IIoT human-machine interface immediately and uses complete and convenient industrial IIoT cloud platform service.








#### Appearance




**Product specifications**


Hardware parameter	Display	10.1" 16:9 TFT LCD
	Resolution (WxH)	1024×600
	Colors	24-bit
	Brightness	400 cd/m <sup>2</sup>
	Backlight	LED
	LCD Life	50000 hours
	Touch Panel	4 wires resistive touch screen
	CPU	600MHz ARM Cortex-A8
	Memory	128M Flash + 128M DDR3
	RTC	Built in
	Ethernet	1 way 10M/100M adaptive
	SD card Port	Available
	USB Port	USB Slave 2.0 port*1,USB Host 2.0 port*1
	Download Project	USB Slave/U disk / Ethernet
	COM Port	COM1/COM3:RS232/RS485/RS422 COM2:RS485
LCD viewing angle (T/B/L/R)	85'/85'/85'/85'	
Electrical Specifications	Power Consumption	< 10W
	Input Power	DC24V, working range DC 9V~28V
	Power Protection	Protected from thunderstrike and surging
	Power Down Allowed	< 5mS
	CE & RoHS	Complied with EN61000-6-2:2005, EN61000-6-4:2007, RoHS, Surge Immunity:±1KV, EFT:±2KV,ESD:4KV, Air:8KV
Environmental Specifications	Operating Temperature	0~50°C
	Storage Temperature	-20~60°C
	Anti-UV	Not suitable to work in strong ultraviolet light (such as direct sunlight)
	Operating Humidity	10~90%RH(non condensate)
	Vibration Endurance	10~25Hz (X,Y,Z direction 2G/30 minutes)
	Cooling	Natural air cooling
Mechanical index	Degree of Protection	Front IP65(with NEMA panel),Back IP20
	Enclosure	Engineering plastic
	Panel Cutout	260mm×202mm
	Dimension	273mm×213mm×36mm
	Weight	About 920g

## Wiring definition


		
Power terminal (Pin1~Pin3 from left to right)		
	Pin1	FG
	Pin2	0V
	Pin3	DC24V
DB9 Serial terminal		
	Pin1	Rx-(B)
	Pin2	RxD (COM1 RS232)
	Pin3	TxD (COM1 RS232)
	Pin4	Tx-
	Pin5	GND
	Pin6	Rx+(A)
	Pin7	RxD (COM3 RS232)
	Pin8	TxD (COM3 RS232)
	Pin9	Tx+
485 terminal (Pin1~Pin2 from left to right)		
	Pin1	A+ (COM2 RS485)
	Pin2	B- (COM2 RS485)
Ethernet port		
	RJ45	Used for Ethernet setup with the controller or for connecting to a server
USB Host		
	USB Type A	Used to connect U disk, scan code gun and other peripherals
USB Slave		
	MicroUSB	Used to download programs and debug

 <p>IIoT Expanding Module Connection</p>	<p>Expansion module card slot</p>	<p>Support module: FLink, FLink-2G, FLink-4G, FLink-WiFi</p>
---	---	--

Size FE6100CE



Size FE6100CE+FLink



**Contact us**

---

**Shanghai (R&D Center)**

Address: Floor 11, Block B, INNO Center,  
No.298, Guoxia Road,  
Yangpu District, Shanghai

Telephone: +86-21-68683993

Fax: +86-21-65107569

**Suzhou**

Address: Room 915, Ricky Building,  
No.668,YutingAvenue,Suzhou  
Industrial Park

Telephone: +86-512-69833996

**Shenzhen (Factory)**

Address: 5th Floor, NO.2 Building,  
Lanyun Science Park, Tangtou  
Road, Shiyan Town, Baoan  
District, Shenzhen, China

Telephone: +86-755-27610682

Fax: +86-755-27629895

**Wuxi**

Address: Room 1603, Taihu  
Mingzhu Development  
Building, No. 1890 Taihu  
West Road, Binhu  
District, Wuxi City

Telephone: +86-18505101982

**Beijing**

Address: Room 2008, Building 1, No. 93  
Jianguo Road, Chaoyang  
District, Beijing (Wanda Plaza)

Telephone: +86-10-58204608

Fax: +86-10-58204608

**Hangzhou**

Address: Floor 1, Unit LEO, Block  
5, Singapore Science  
Park, Road 6th, Xiasha  
Economic Development  
Zone, Hangzhou