


Variant key 4mm



Type	Displacement cm ³ /rev	Flow		Pressure P _{nom} bar	max Speed n rpm	Dimension									
		at 1500 rpm l/min	at max rpm l/min			Inlet		Outlet							
						A mm	B mm	M	G	G1	M	G	G1		
20A(C)4,5X016...	4,5	6,14	14,33	250	3500	42,5	80	M20x1,5	G1/2						
20A(C)6,3X016...	6,3	8,69	20,29	250	3500	42,5	80								
20A(C)8,2X016...	8,2	11,32	26,40	250	3500	42,5	80								
20A(C)10X016...	10	13,95	32,55	250	3500	47	89		G3/4					M16x1,5	
20A(C)11X016...	11,3	15,76	36,78	250	3500	48	91,1								
20A(C)12X016...	12	16,92	39,48	250	3500	48,6	92,3		G1						G1/2
20A(C)14X016...	14	19,95	46,55	250	3500	50	95,4								
20A(C)15X016...	15	21,60	36,00	250	2500	51	96,9								M20x1,5
20A(C)16X016...	16	23,04	38,40	250	2500	52	98,6								
20A(C)19X016...	19	27,36	45,60	200	2500	54	103,5								G3/4
20A(C)22X016...	22	31,68	42,24	180	2000	57	108,5								
20A(C)25X016...	25	36,00	48,00	160	2000	59,2	113,4								
20A(C)14X016H	14	20,16	47,04	250	3500	55,3	105,7	M20x1,5		G3/4					
20A(C)15X016H...	15	21,60	43,20	250	3000	56	107,2								
20A(C)16X016H...	16	23,04	46,08	250	3000	56,9	108,8		M16x1,5						
20A(C)17,3X016H...	17,3	24,91	49,82	230	3000	58	110,9								
20A(C)18,2X016H...	18,2	26,21	52,42	210	3000	58,8	112,5		G1/2						
20A(C)19X016H...	19	27,36	54,72	200	3000	59,4	113,8								
20A(C)22X016H...	22	31,68	52,80	180	2500	61,9	118,8		M20x1,5						
20A(C)25X016H...	25	36,00	60,00	160	2500	64,3	123,7								
20A(C)28X016H...	28	40,32	67,20	130	2500	66,8	128,5		G3/4						
20A(C)32X016H...	32	46,08	61,44	120	2000	70	134,8								
20A(C)36X016H...	36	51,84	69,12	100	2000	73,2	141,4	M27x2	G1						