

Junction box

# HP 150-L



## HP 150-L

### Junction box

Productnumber: 32695001  
Dimensions: 164 x 119 x 77 mm

Junction box,  $U_i=690V$ , 10 recessed stepped nipples, seal range 5 - 21 mm

**Grey, without terminals, with cover retainer**



## Technical Data

### electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Type of protection:	IP55
Circuit integrity class:	none
Max. conductor cross section:	10 mm <sup>2</sup>
Protection class:	II

### Dimensions

Length:	119 mm
Width:	164 mm
Height:	77 mm
Inner length:	110 mm
Inner width:	155 mm

### Dimensions

Inner height:	70 mm
---------------	-------

### Material characteristics

suitable for exterior use:	no
Halogen free:	no
Industry quality:	no

### mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	no
Impact strength:	IK07

## Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25
Max. ambient temperature:	40
24h ambient temperature:	35

## Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

## Certificates

Test mark:	VDE
------------	-----

## Accessories

NS 35-106 - Standard rail

NS 35-144 - Standard rail

SNI M25 - Stepped nipple

KVR M25-MGM - Cable gland

WK 100 KLS-10<sup>2</sup> - Terminal block

NS 35-90 - Standard rail