

Tractor Radial • Characteristics of TA 130 /70

Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
			Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
										10	30	40	50	65
710/70 R42	TL	173 D / 176 A8	DW23B	-	716	2061	6183	891	9 / 0.6	4280	3515	3340	3210	3055
									12 / 0.8	4915	4040	3835	3690	3510
									15 / 1.0	5645	4635	4405	4235	4030
									17 / 1.2	6370	5235	4970	4780	4550
									20 / 1.4	7100	5835	5540	5325	5070
									23 / 1.6	7830	6430	6110	5870	5590
									26 / 1.8	8190	6730	6390	6145	5850
									28 / 1.9	8375	6880	6535	6280	5980
									29 / 2.0	8555	7030	6675	6420	6110
									32 / 2.2	8830	7255	6890	6625	6305
35 / 2.4	9100	7475	7100	6825	6500									



DESCRIPTION

- * For load capacity on various speed ratings, and inflation figures, please consult your sales representative.
- ** Load capacity on standard speed and weight
- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.