

Tractor Radial • Characteristics of TA 130¹⁷⁰

Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
			Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
										10	30	40	50	65
710/70 R38	TL	171 D / 174 A8	DW23B	-	716	1959	5877	941	9 / 0.6	4050	3325	3150	3040	2895
									12 / 0.8	4650	3820	3620	3490	3325
									15 / 1.0	5340	4385	4155	4005	3815
									17 / 1.2	6030	4955	4690	4525	4305
									20 / 1.4	6720	5520	5230	5040	4800
									23 / 1.6	7405	6085	5765	5555	5290
									26 / 1.8	7750	6370	6030	5815	5535
									28 / 1.9	7925	6510	6165	5945	5660
									29 / 2.0	8095	6650	6300	6075	5785
									32 / 2.2	8355	6865	6500	6265	5970
								35 / 2.4	8610	7075	6700	6460	6150	
800/70 R38	TL	178 D / 181 A8	DW25B	DW27B	795	2055	6090	905	9 / 0.6	4935	4055	3880	3705	3525
									12 / 0.8	5670	4660	4455	4255	4050
									15 / 1.0	6510	5350	5115	4885	4650
									17 / 1.2	7350	6040	5775	5515	5250
									20 / 1.4	8190	6730	6435	6145	5850
									23 / 1.6	9030	7420	7095	6775	6450
									26 / 1.8	9450	7765	7425	7090	6750
									28 / 1.9	9660	7935	7590	7245	6900
									29 / 2.0	9870	8110	7755	7405	7050
									32 / 2.2	10185	8370	8005	7640	7275
								35 / 2.4	10500	8625	8250	7875	7500	
620/70 R42	TL	166 D	DW20B	-	625	1971	5913	891	9 / 0.6	3490	2865	2730	2620	2495
									12 / 0.8	4010	3295	3135	3010	2865
									15 / 1.0	4605	3780	3600	3455	3290
									17 / 1.2	5195	4270	4065	3900	3710
									20 / 1.4	5790	4755	4530	4345	4135
									23 / 1.6	6385	5245	4995	4790	4560
									26 / 1.8	6680	5490	5225	5010	4770
									28 / 1.9	6830	5610	5340	5120	4880
									29 / 2.0	6975	5730	5460	5235	4985
									32 / 2.2	7200	5915	5630	5400	5145
								35 / 2.4	7420	6095	5805	5565	5300	

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.