

# Tractor Radial • Characteristics of TA 130 /70

Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
			Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
										10	30	40	50	65
600/70 R28	TL	161 D	DW20B	DW18L, W18L	591	1551	4653	692	9 / 0.6	2715	2230	2125	2040	1940
									12 / 0.8	3120	2565	2440	2340	2230
									15 / 1.0	3585	2945	2805	2690	2560
									17 / 1.2	4045	3325	3165	3035	2890
									20 / 1.4	4505	3705	3525	3380	3220
									23 / 1.6	4970	4080	3885	3725	3550
									26 / 1.8	5200	4270	4070	3900	3715
									28 / 1.9	5315	4365	4160	3985	3795
									29 / 2.0	5430	4460	4250	4075	3880
									32 / 2.2	5605	4605	4385	4205	4005
<b>35 / 2.4</b>	<b>5775</b>	<b>4745</b>	<b>4520</b>	<b>4335</b>	<b>4125</b>									
600/70 R30	TL	158 D	DW20B	DW18L, W18L	591	1602	4806	717	9 / 0.6	2800	2300	2190	2100	2000
									12 / 0.8	3215	2640	2515	2410	2295
									15 / 1.0	3690	3035	2890	2770	2635
									17 / 1.2	4165	3425	3260	3125	2975
									20 / 1.4	4645	3815	3630	3485	3315
									23 / 1.6	5120	4205	4005	3840	3655
									26 / 1.8	5355	4400	4190	4020	3825
									28 / 1.9	5475	4500	4285	4110	3910
									29 / 2.0	5595	4595	4375	4195	3995
									32 / 2.2	5775	4745	4515	4330	4125
<b>35 / 2.4</b>	<b>5950</b>	<b>4890</b>	<b>4655</b>	<b>4465</b>	<b>4250</b>									
600/70 R34	TL	160 D	DW18L	DW20B, W18L	591	1723	5169	776	9 / 0.6	2965	2435	2320	2225	2115
									12 / 0.8	3405	2795	2665	2555	2430
									15 / 1.0	3910	3210	3060	2930	2790
									17 / 1.2	4410	3625	3450	3310	3150
									20 / 1.4	4915	4040	3845	3690	3510
									23 / 1.6	5420	4455	4240	4065	3870
									26 / 1.8	5670	4660	4435	4255	4050
									28 / 1.9	5800	4765	4535	4350	4140
									29 / 2.0	5925	4865	4635	4445	4230
									32 / 2.2	6115	5020	4780	4585	4365
<b>35 / 2.4</b>	<b>6300</b>	<b>5175</b>	<b>4930</b>	<b>4725</b>	<b>4500</b>									

## DESCRIPTION

\* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

\*\* Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.