

Tractor Radial • Characteristics of TA 110/85

Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg			
			Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h			
										10	30	40	50
420/85 R28	TL	139 A8 / 136 B	W15L	W13, W14L	418	1425	4261	635	9 / 0.6	1795	1435	1340	1220
									12 / 0.8	2085	1665	1560	1420
									15 / 1.0	2380	1900	1775	1615
									17 / 1.2	2675	2135	1995	1815
									20 / 1.4	2965	2370	2215	2015
23 / 1.6	3260	2605	2430	2240									
380/85 R30	TL	135 A8 / 132 B	W12	W11, W13	380	1404	4236	634	9 / 0.6	1610	1285	1200	1095
									12 / 0.8	1870	1495	1400	1270
									15 / 1.0	2135	1705	1595	1450
									17 / 1.2	2400	1915	1790	1630
									20 / 1.4	2660	2125	1985	1810
23 / 1.6	2925	2335	2180	2000									
420/85 R30	TL	140 A8 / 137 B	W15L	W13, W14L	420	1475	4455	660	9 / 0.6	1845	1475	1375	1255
									12 / 0.8	2145	1715	1600	1460
									15 / 1.0	2450	1955	1825	1665
									17 / 1.2	2750	2195	2050	1870
									20 / 1.4	3050	2435	2275	2075
23 / 1.6	3350	2675	2500	2300									
460/85 R30	TL	145 A8 / 142 B	W16L	W14L, W15L	455	1544	4683	694	9 / 0.6	2140	1710	1595	1455
									12 / 0.8	2490	1990	1860	1690
									15 / 1.0	2840	2270	2120	1930
									17 / 1.2	3190	2545	2380	2165
									20 / 1.4	3540	2825	2640	2405
23 / 1.6	3890	3105	2900	2650									

• Load capacity on recommended speed and pressure is stated with dark colour.

DESCRIPTION

* For load capacity on various speed ratings, and inflation figures, please consult your sales representative.

** Load capacity on standard speed and weight

- Our company is entitled to make any change on any information in this catalogue, without further notice.
- This catalogue annuls all the previous catalogues
- All figures are for reference; our company is not responsible for printing errors.