

Tractor Radial • Characteristics of TA 110/65

Tire Size	TT/TL	Load/Speed Index	Rims		Inflated Dimensions (No Load)		Inflated Dimensions (W/Load)		Inflation Pressure (psi/bar)	Load capacity per tire, kg				
			Recom (inch)	Permitted (inch)	Section Width (mm)	Outer Diameter (mm)	Dynamic Rolling Circumference (mm)	Static Loaded Radius (mm)		Speed, km/h				
										10	30	40	50	65
480/65 R28	TL	136 D/139 A8	W15L	W14L	475	1356.3	4035	605	9 / 0.6	1685	1445	1375	1320	1255
									12 / 0.8	1985	1705	1620	1555	1480
									15 / 1.0	2255	1935	1840	1765	1680
									17 / 1.2	2525	2165	2065	1980	1885
									20 / 1.4	2765	2370	2260	2165	2065
23 / 1.6	3005	2580	2430	2355	2240									
540/65 R28	TL	149 D/152 A8	W16L	W18L	535	1430.7	4248	637	9 / 0.6	2440	2095	1995	1915	1820
									12 / 0.8	2875	2470	2350	2255	2145
									15 / 1.0	3270	2805	2670	2560	2440
									17 / 1.2	3660	3140	2990	2870	2730
									20 / 1.4	4010	3440	3275	3140	2990
23 / 1.6	4355	3740	3550	3415	3250									
540/65 R30	TL	150 D/153 A8	W16L	W18L	534.5	1477.2	4390	664	9 / 0.6	2515	2160	2055	1970	1880
									12 / 0.8	2965	2545	2425	2325	2215
									15 / 1.0	3370	2890	2755	2640	2515
									17 / 1.2	3775	3240	3085	2955	2815
									20 / 1.4	4130	3545	3375	3240	3085
23 / 1.6	4490	3855	3650	3520	3250									
540/65 R34	TL	145 D/148 A8	W16L	W18L	535	1568	4698	711	9 / 0.6	2180	1870	1780	1710	1625
									12 / 0.8	2565	2205	2100	2010	1915
									15 / 1.0	2915	2505	2385	2285	2175
									17 / 1.2	3265	2805	2670	2560	2440
									20 / 1.4	3580	3070	2925	2805	2670
23 / 1.6	3890	3335	3150	3045	2900									
600/65 R34	TL	151 D/154 A8	DW20B	W18L	591	1665.7	4897	741	9 / 0.6	2590	2225	2120	2030	1935
									12 / 0.8	3055	2620	2495	2395	2280
									15 / 1.0	3470	2980	2835	2720	2590
									17 / 1.2	3885	3335	3175	3045	2900
									20 / 1.4	4255	3655	3480	3335	3175
23 / 1.6	4625	3970	3750	3625	3450									