


SmartLogger3000A



Smart

Smart zero export control design



Simple

Easy to install on site



Reliable

Safety by lightning protection module

| Technical Specification | SmartLogger3000A |
|------------------------------------|--|
| Device Management | |
| Max. Number of Connected Devices | 80 |
| Communication Interface | |
| WAN | WAN x 1, 10 / 100 / 1000 Mbps |
| LAN | LAN x 1, 10 / 100 / 1000 Mbps |
| RS485 | COM x 3, 1,200 / 2,400 / 4,800 / 9,600 / 19,200 / 115,200 bps |
| MBUS | MBUS x 1, 115.2 kbps, Compatible with PLC |
| 2G / 3G / 4G | LTE (FDD) : B1, B2, B3, B4, B5, B7, B8, B20 DC-HSPA+ / HSPA+ / HSPA / UMTS : 850 / 900 / 1,900 / 2,100 MHz GSM / GPRS / EDGE: 850 / 900 / 1,800 / 1,900 MHz ² |
| Digital / Analog Input / Output | DI x 4, DO x 2, AI x 4 |
| Active DO | 12V, 100mA (connection with relay, sensor) |
| Communication Protocol | |
| Ethernet | Modbus-TCP, IEC 60870-5-104 |
| RS485 | Modbus-RTU, IEC 60870-5-103 (standard), DL / T645 |
| Interaction | |
| LED | LED Indicator x 3 – RUN, ALM, 4G |
| WEB | Embedded Web |
| USB | USB 2.0 x 1 |
| APP | Communication by WLAN for Commissioning |
| Environment | |
| Operating Temperature Range | -40°C ~ 60°C (-40°F ~ 140°F) |
| Storage Temperature | -40°C ~ 70°C (-40°F ~ 158°F) |
| Relative Humidity (Non-condensing) | 5% ~ 95% |
| Max. Operating Altitude | 4,000 m (13,123 ft.) |
| Electrical | |
| AC Power Supply | 100 V ~ 240 V, 50 Hz / 60 Hz |
| DC Power Supply | 12 V / 24 V |
| Power Consumption | Typical 8 W, Max. 15 W |
| Mechanical | |
| Dimensions (W x H x D) | 225 x 160 x 44 mm (8.9 x 6.3 x 1.7 inch, without mounting ears and antenna) |
| Weight | 2 kg (4.4 lb.) |
| Protection Degree | IP20 |
| Installation Options | Wall Mounting, DIN Rail Mounting, Tabletop Mounting |

1: When putting inside metal box, extended antenna will be needed.

2: For recommended carriers list and details on supported frequencies, please contact local distributors.