

## RID 8 E-SERIES S

### ANTI VANDAL GENSET 8 KVA



#### POWER RATING

OUTPUT RATINGS		PRIME	STANDBY
Power	kVA   kW	8   6,3	8,8   6,9
Current	A	11,5	12,6
Voltage	V	230 / 400	230 / 400
Frequency	Hz	50	
Rated at power factor	cos φ	0,8	

#### POWER RATING DESCRIPTION

##### Prime Rating

The ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

##### Standby Rating

The ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

#### PRODUCT OVERVIEW

RATINGS DATA	
Order number Generator	713111
Alternator Model	Meccalte ECP 3-2S/4
Engine Type	MITSUBISHI - L3E
Generator type	synchronous
Protection class	IP 23
Control Panel	RID 1000 A

#### DIMENSIONS AND WEIGHTS

LENGTH (L)	WIDTH (W)	HEIGHT (H)	WEIGHT	TANK CAPACITY
1650 mm	1100 mm	1575 mm	595 kg	up to 1000 liters

#### NOISE LEVEL

1 METER	4 METER	7 METER	10 METER
72 dB(A)	63 dB(A)	59 dB(A)	56,5 dB(A)

## RID 8 E-SERIES S

### ANTI VANDAL GENSET 8 KVA



#### ENGINE TECHNICAL DATA

ENGINE TECHNICAL DATA		PRIME
Engine output	kW	6,3
Engine type		MITSUBISHI - L3E
Engine size		3-Cylinder; in-line
Injection system		Inline diesel injection pump
Rotational-speed range	rpm	1500
Bore   Stroke	mm	78   92
Cooling system		water + air
Speed regulation		mechanical
Compression ratio		23:1
Displacement	l	0,95
Engine w/o cooling system	kg	90

#### FUEL SYSTEM

POWER STANDARD		25%	50%	75%	100%
Fuel consumption PRIME	l/h	0,8	1,3	1,8	2,2

#### EXHAUST SYSTEM

Silencer type		Industrial
Max. exhaust back pressure	mbar	65
Exhaust gas flow	m <sup>3</sup> /h	108

#### LUBRICATION SYSTEM

Oil type		RID 10W40
Oil filter type		replaceable element
Total oil volume	l	4,7

#### COOLING SYSTEM

Cooling system		water + air
Cooling system capacity (Engine)	l	1,8
Fan power consumption	kW	0,1

#### AIR SYSTEM

Air Filter Type		replaceable Element
Combustion air volume	m <sup>3</sup> /h	39
max. intake depression	mbar	19,6

## RID 8 E-SERIES S

### ANTI VANDAL GENSET 8 KVA



#### ALTERNATOR DATA

<b>Alternator Model</b>	Meccalte ECP 3-2S/4	
<b>Generator type</b>	synchronous	
<b>Insulation Class</b>	H	
<b>Regulation Type</b>	±1 % with any power factor and speed variations between -5% +30%	
<b>Control System</b>	self excited	
<b>Execution</b>	brushless	
<b>Protection class</b>	IP 23	
<b>Stator Winding</b>	12 ends	
<b>Rotor Winding</b>	I	with damping cage
<b>Short Circuit Current Capacity</b>	>300%	
<b>THD at full load</b>	2,8%	
<b>Overspeed</b>	rpm	2250
<b>Air Flow Requirement</b>	m <sup>3</sup> /h	210
<b>References</b>	EN61000-6-3	EN61000-6-2

#### ALTERNATOR PERFORMANCE DATA

VOLTAGE SERIES STAR, V	RATED POWER (125°C/40°C), KVA   KW	X <sub>d</sub>	X' <sub>d</sub>	X'' <sub>d</sub>
380	8   6,4	201,7 %	18,2 %	13,1 %
400	8   6,4	182 %	16,4 %	11,8 %
415	8   6,4	169,1 %	15,2 %	11 %
440	6,8   5,4	127,9 %	11,5 %	8,3 %

#### CERTIFICATIONS AND NORMS

EN60034-1	ISO8528-3	EN55011	Outdoor Noise Equipment Directive 2000/14/EC
-----------	-----------	---------	--

## RID 8 E-SERIES S

### ANTI VANDAL GENSET 8 KVA



#### CONTROL PANEL

~ RID 1000 A ~

#### CONTROLLER FUNCTIONS

FUNCTIONS	RANGES, VALUES	
<b>operating modes</b>	automatic, manual, test and remote	available
<b>mains control with limits</b>	voltage, frequency, phase sequence	available
<b>generator control with limits</b>	voltage, frequency, power, phase sequence.	available
<b>engine control with limits</b>	start, stop, shutdown by alarms	available
<b>power control</b>	current, kW, kVA, kVA <sub>r</sub> , power factor	available
<b>statistic data mains</b>	voltage, frequency and current	available
<b>statistic data generator</b>	voltage, frequency and current	available
<b>fuel level control</b>	in % and in liters	available
<b>fuel consumption control and history</b>	in l/h	available
<b>working hours per day</b>	in h	available
<b>service hours</b>	in h	available
<b>battery service</b>	in h	available
<b>events log with time and date</b>	255 events	available
<b>alarm list programming</b>	77 alarms	available
<b>protocols</b>	GSM, Ethernet, Modbus, Canbus, RID protocol	available

#### REMOTE MONITORING FUNCTIONS

<b>mains voltage L1, L2, L3</b>	in V, AC	available	<b>engine temperature</b>	in °C,	optional
<b>generator voltage L1, L2, L3</b>	in V, AC	available	<b>enviroment temperature</b>	in °C,	optional
<b>genset battery voltage DC</b>	in V, DC	available	<b>generator run hours</b>	in h,	available
<b>mains power total</b>	in kW,	available	<b>generator maintanace hours</b>	in h,	available
<b>generator power total</b>	in kW,	available	<b>fuel level</b>	in L,	available
<b>mains frequency</b>	in Hz	available	<b>load on mains</b>	indication	available
<b>generator frequency</b>	in Hz	available	<b>load on generator</b>	indication	available
<b>current L1, L2, L3</b>	in A,	available	<b>mains supply</b>	indication	available
<b>power L1, L2, L3</b>	in kW,	available	<b>generator supply</b>	indication	available

#### SPECIFIC ALARMS

GENSET DOOR OPEN	FUEL TANK OPEN	AIR FILTER CLOGGING	FIRE ALARM
optional	optional	optional	optional