

# AD1/AP-1A

miniaturized cylindrical inductive




Micro Detectors

Italian Sensors Technology



Indicative image



1 LED

## Detection properties

Nominal sensing distance	0,8mm
Operanting distance	0...0,65mm
Standard target	4x4mm FE360
Correction Factor	copper: 0,32 ± 10% / aluminium: 0,26 ± 10% / brass: 0,35 ± 10% / stainless steel: 0,66 ± 10%
Thermal drift of Sr	< 10%
Repeat Accuracy	5% (UB 24V Ta=23°C ±5°C)
Hysteresis	1 ... 20%

## Outputs

Output type	PNP
Output Function	NO
Switching frequency	5kHz

## Electrical data

Operating Voltage	10...30Vdc
No-Load supply current	≤ 10mA
Load current	≤ 100mA
Leakage current	≤ 10µA

Output voltage drop	≤ 1,5V @100mA
Max ripple content	≤10%
LED indicators	Yellow LED output state
Time delay before availability	≤ 50ms
Short-circuit protection	Yes (auto-reset)
Reverse Polarity Protection	Yes
Protection against inductive loads	Yes

## Mechanical data

Mounting	Shielded
Dimensions	M5 x 0,5 / L = 30,2mm
Weight	30g
Housing Material	AISI 303 Stainless Steel
Connections	2m PVC Cable
Active Head Material	PBT
Tightening torque	2Nm
Operating temperature	-25°C...+70°C
Diameter/Dimension	M5

## Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	Vibration IEC 60068-2-6 / Shock IEC 60068-2-27
Degree of protection	IP67


## Accessories

Supplied Accessories	2 nuts M5x0,5
----------------------	---------------

---


# ELECTRICAL DIAGRAMS OF THE CONNECTIONS

---



## INSTALLATION

---




<sup>(1)</sup> ≥ 1 mm without ferro-magnetic material

## RESPONSE CURVES

---

Disassamento Parallelo



**M.D.Micro Detectors S.p.A.**

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail [info@microdetectors.com](mailto:info@microdetectors.com)

**date of printing**

20/11/2020 14:41:25