Product Information 01.20.11

10-12-2020

Bi-Turbo 20W-50

Description

Bi-Turbo 20W-50 is a universal, mineral motor oil based on premium solvent-refined base oils. It is supplemented with additives to achieve the following properties:

- Very powerful detergency and dispersion thereby preventing a high build-up of black sludge
- Very high resistance to oxidation
- Highly effective against wear
- Good resistance to corrosion and foaming
- A high and stable viscosity index
- A low tendency to evaporate
- No negative influence on catalytic converters

Application

Bi-Turbo 20W-50 is a universal mineral motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine or catalytic convertor. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

ACEA A3/B4
API SL/CF
MB 229.1
VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,890
Viscosity -15 °C, mPa.s	9000
Viscosity 40 °C, mm²/s	164,00
Viscosity 100 °C, mm²/s	17,90
Viscosity Index	120
Flash Point COC, °C	238
Pour Point, °C	-24
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,29

Available packagings

00221 1 L bottle	33079 4 L can	00340 5 L can	32902 20 L Bag in Box	35063 20 L pail	35117 20 L can	10133 60 L drum	34752 200 L drum	10238 208 L drum